TIONS

REPORT ON BEGINNING DRILLING OPERA-

Santa Fe, New Mexico

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within terms specified is completed. It should be signed and sworn to before a notary public for reports on attentions, results of shooting well, results of test of casing shut-off, result of plugging of well, and of the even though the work was witnessed by an agent of the Commission. Reports on minor operations need and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON REPAIRING WELL

signed

REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING			
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT O	N DEEPENI	NG WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X				
	Lubboo	ok, Texas		7-19-50	ate
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:		Tiace		•	
Following is a report on the work done and the resu George P. Livermore, Inc. R.	W. Cow	ien	Wall	No. 2	in the
SE/4 Company or Operator of Sec. 39	. (Lease 23S T.	. R.	37E	, N. M . P. M.,
Langlie-Mattix Field,		Lea 9-50			
The dates of this work were as follows:				710-8	
Notice of intention to do the work was (was not) s	ubmitted	on Form C-102	? on	7-19-50*	1950
DETAILED ACCOUNT OF *Approval recaived by tel Total depth - 3655*. 5-1/2* ca	Lephone	7-19-50. et @ 3447'.	. Plugged	with 25 sa	u x
*Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit h" mar ker as required.	asing so alled 30 th 10 so	7-19-50. at @ 3447† 000† of 5- ax cement	1/2" casin from 1200'	g. Set sec to 1175'.	eond Used
Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit h" mar ker as required.	asing so alled 30 th 10 so	7-19-50. at @ 3447 000* of 5-1 ax cement;	1/2" casin from 1200'	g. Set sec to 1175'.	ond .
Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit has mar ker as required. Witnessed by C. E. Witten Name Subscribed and sworn before me this	dephone asing stalled 30 th 10 at	7-19-50. at @ 3447 000* of 5-; ax cement; rge P. Liv	1/2" casin from 1200' ermore, In	to 1175.	ond Used tion Foreman
*Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit li" mar ker as required. Witnessed by	Geo:	7-19-50. et @ 3447' 000' of 5- ax cement rge P. Live Con hereby swear s true and corr	1/2" casin from 1200' ermore, In	to 1175. ac. Product	Used tion Foreman
*Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit hi mar ker as required. Witnessed by	Geo.	7-19-50. et @ 3447' 000' of 5- ax cement rge P. Live Con hereby swear s true and corr Name	crmore, Ir apany or affirm the rect. Chief Eng	to 1175. The production of the information of the	Used Used Stion Foreman Title Sion given above
*Approval recaived by tel Total depth - 3655'. 5-1/2" ca cement from 3655' to 3430'. Pu plug in 8-5/8" surface pipe wit has mar ker as required. Witnessed by	Geo:	7-19-50. et @ 3447' 000' of 5- ax cement rge P. Live Con hereby swear s true and corr Name Position	crmore, Ir apany or affirm the rect. Chief Eng	to 1175. at the informat	tion Foreman

The state of the s The state of the s - Angle - An

The second control of the second control of

And the second of the second o