

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

RECEIVED
AUG 8 - 1940
HOBBS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	XX
NOTICE OF INTENTION TO DEEPEN WELL			

Jal, New Mexico

August 7th, 1940

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____
WESTERN GAS COMPANY **R. W. Cowden** Well No. **4** in **NE NE NE 1/4**
 Company or Operator **31** **23 S. 37E.** **Skelly**
 of Sec. **1**, T. _____, R. _____, N. M. P. M., _____ Field,
Lea _____ County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Elev. 3321
T. D. 3570
Production, Zero.

Will fill hole to 7" casing seat at 3440 with cement. After cement has set, 7" will be filled with mud and shot off at approximately 2000'. Casing will be pulled while hole is loaded with heavy mud. A cement plug will then be set at the 9-5/8" casing seat at 1269', the casing will be shot off at about 500', and pulled while the hole is filled with mud. The 13" casing which is set at 203' will remain in the hole as it is cemented to the surface. The hole will then be filled with very heavy mud to the cellar floor, and a 4" pipe will be cemented in the bottom of the cellar with 10 sacks of cement and will extend 4' above ground surface as a marker. The cellar will then be filled level with the surface.

7 1/2 shot off
2539' -
open to
1269'

AUG 8 - 1940

Approved _____, 19____
except as follows:

WESTERN GAS COMPANY

Company or Operator
By **E. C. Kimball**

Position **Ass't. Petroleum Engr.**
Send communications regarding well to

Name **W. K. Davis, Prod. Sup't.**
Address **P. O. Box 1981, Jal, New Mexico**

OIL CONSERVATION COMMISSION,
By **Roy Yankrough**
Title **OIL & GAS INSPECTOR**

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000

SECTION 800.000.000