## NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and

Regulations of the Commission.  Indicate nature of no	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	
NOTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL
Hobbs, New Me:	xico Sept. 21, 1939 Place Date
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.	DUPLICATE
Gentlemen:	
Following is a notice of intention to do certain work as  Repollo Gil Company	described below at the
Company or Operator Lease	
	, N. M. P. M., Skelly Field
County,	103590
FULL DETAILS OF PR 3321 FOLLOW INSTRUCTIONS IN THE RULE	OPOSED PLAN OF WORK S AND REGULATIONS OF THE COMMISSION
off 7"0" Casing at approximately and 7"0" casing. ement plug in bottom of 9 5/8"0" ca	2000' keeping hole full heavy mud whi asing (15 sacks) set 4 1269', after (
ng 7"OD casing.  ement plug in bottom of 9 5/8"OD casing at appropriate pulling 9 5/8"OD casing. 13"OB ted to surface. Keep hole full hear	eavymud. 2000' keeping hole full heavy mud whi
off 7"0" Casing at approximately and 7"0" casing.  ement plug in bottom of 9 5/8"0" of shoot off 9 5/8"0" casing at approximate pulling 9 5/8"0" casing at approximate pulling 9 5/8"0" casing. 13"0" ted to surface. Keep hole full hear llar with 10 sacks with piece of 4"	eavymud.  2000' keeping hole full heavy mud which asing (15 sacks) set @ 1269', after coximately 500' keeping hole full of hole casing set @ 203' will remain in how mud to bottom of cellar. Cement bottom of cellar.
off 7"0" Casing at approximately and 7"0" casing.  ement plug in bottom of 9 5/8"0" of shoot off 9 5/8"0" casing at approximate pulling 9 5/8"0" casing at approximate pulling 9 5/8"0" casing. 13"0" ted to surface. Keep hole full hear llar with 10 sacks with piece of 4"	eavymud.  2000' keeping hole full heavy mud which asing (15 sacks) set 4 1269', after coximately 500' keeping hole full of heavy mud to bottom of cellar. Cement be pipe cemented in bottom of cellar e
off 7"0" Casing at approximately and 7"0" casing.  ement plug in bottom of 9 5/8"0" of shoot off 9 5/8"0" casing at approximate pulling 9 5/8"0" casing at approximate pulling 9 5/8"0" casing. 13"0" ted to surface. Keep hole full hear llar with 10 sacks with piece of 4"	eavymud. 2000' keeping hole full heavy mud which asing (15 sacks) set a 1269', after coximately 500' keeping hole full of heavy mud to bottom of cellar. Cement be my mud to bottom of cellar. Cement be my mud to bottom of cellar on Marker". Fill cellar level with supplied the same of the same o
off 7"0" Casing at approximately and 7"0" casing.  ement plug in bottom of 9 5/8"0" casing at appropriate pulling 9 5/8"0" casing at appropriate to surface. Keep hole full hear lar with 10 sacks with piece of 4" ove the surface lever as "Regulation" SEP 251939  Approved	eavymud. 2000' keeping hole full heavy mud which asing (15 sacks) set a 1269', after coximately 500' keeping hole full of heaving set a 203' will remain in heavy mud to bottom of cellar. Cement be my mud to bottom of cellar con Marker". Fill cellar level with such marker Fill cellar level with such marker Repollo 011 chors of cellar.
off 7"0D Casing at approximately and 7"0D casing.  ement plug in bottom of 9 5/8"0D casing at appropriate pulling 9 5/8"0D casing. 13"00 ted to surface. Keep hole full hear lar with 10 sacks with piece of 40 ove the surface lever as "Regulation of the surface lever as "Regulation" of the surface lever as "Regulation of the surface lever as "Regulation of the surface lever as "Regulation" of the surface lever as "Regulation of the surface lever as "Regulation" of the surface lever as "Regulation" of the surface lever as "Regulation of the surface lever as "Regulation" of the surface lever	eavymud. 2000' keeping hole full heavy mud which asing (15 sacks) set 4 1269', after coximately 500' keeping hole full of heavy mud to bottom of cellar. Cement be pipe cemented in bottom of cellar on Marker". Fill cellar level with supplied the same of the s
off 7"0" Casing at approximately and 7"0" casing.  ment plug in bottom of 9 5/8"0" casing at appropriate pulling 9 5/8"0" casing. 13"0" ted to surface. Keep hole full hear lar with 10 sacks with piece of 4" ove the surface lever as "Regulation" SEP 251939  Approved	eavymud. 2000' keeping hole full heavy mud which asing (15 sacks) set a 1269', after coximately 500' keeping hole full of heavy mud to bottom of cellar. Cement be mud to bottom of cellar. Cement be mud to bottom of cellar each Marker". Fill cellar level with such marker.
off 7"0" Casing at approximately and 7"0" casing.  ement plug in bottom of 9 5/8"0" casing at appropriate pulling 9 5/8"0" casing at appropriate to surface. Keep hole full hear lar with 10 sacks with piece of 4" ove the surface lever as "Regulation" SEP 251939  Approved	Repollo Oil CHORRS OFFI  Company or Operator  Position  Dist. Supt.
off 7"OD Casing at approximately and 7"OD casing.  ement plug in bottom of 9 5/8"OD casing at appropriate pulling 9 5/8"OD casing. 13"OB ted to surface. Keep hole full hear lar with 10 sacks with piece of 4"ove the surface lever as "Regulation" SEP 251939  Approved	Repollo Oil CHORRS OFFICE  Company or Operator  By  Position  Dist. Supt  Send communications regarding well to

en de la companya de la co • ž ,

1. 1. 3. 18 1 B. 18 1