

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	31	31	Caliche
31	160	129	Sand
160	580	390	Red Bed
580	610	60	Sand
610	675	65	Red Rock
675	780	105	Sand
780	810	30	Shale
810	824	14	Sand
824	1209	375	Red Rock
1200	1275	75	Anhydrite
1275	1295	15	Salt
1295	1380	85	Anhydrite
1380	1565	185	Salt & Shells
1565	1592	27	Anhydrite
1592	2099	507	Salt & Anhydrite
2099	2240	141	Salt
2240	2720	480	Salt & Anhydrite
2720	2850	130	Lime & Anhydrite
2850	3494	614	Lime
3494	3512	18	Sandy Lime (Shale Break 3502-09)
3512	3513	1	Shale
3513	3527	14	Lime
3527	3550	23	Sandy Lime (Showing Oil & Gas 3530-04) Increase in oil - 3550
3550	3560	10	Sand (Oil)
3560	3562	2	Sand- soft
3562	3575	14	Lime- hard
3575	3583	7	Lime, sandy (1300' oil in hole)
3583	3600	17	Lime- hard (Well flowed while pulling tools)
3600	3611	11	Sand & Lime
3611	3618	7	Lime- hard (2000' oil in hole)
3618	3620	2	Lime- Soft Dark Gray
3620	3637	17	Lime
3637	3644	7	Lime & Sand
3644	3675	31	Lime
3675	3689	14	Sandy Lime
3689	3710	21	Lime
3710	3714	4	Sandy Lime
3714	3840	126	Lime
3840	3850	10	Blue Lime - Sulphur water - 3850'
PLUGGED HOLE BACK			
3850	3815	35	With Gravel & Lead 200'
3815	3570	245	With Gravel & Lead 200'
	3570		Total plug back depth Bottom Hole water shut off