

Form 9-331
Dec. 1973

O+5 - USGS - P.O. Box 1857

1 - Engr. - LM, RH 11 - WIO's 1 - File

Roswell, NM 88201

1 - Foreman HC

Form Approved.

Budget Bureau No. 42-R1424

UNITED STATES 1-Laura Rich.

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit ltr. P, 660' FSL, 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☒(other) ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. TIH with 1" tubing to 3665' (swage if required).
2. Spot 10 sxs. class "C" cement 3665'-3265' (perfs at 3542'-3648').
3. Spot 40 sxs. class "C" cement 2800'-~~1200'~~ 1100'
4. Spot 10 sxs. class "C" cement at surface.
5. Install permanent marker.

Note: This is a slim-hole completion with 2 7/8" casing.
For this well, the 2 7/8" casing has been cemented to 500'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Area Superintendent DATE 11-24-82APPROVED (Orig. Sgd.) [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

DEC 10 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

NOV 30 1982