


NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		Notice of Intention to Plug and Abandon	X

Hobbs, New Mexico

July 8, 1948

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Gulf Oil Corporation Edith D. Fanning "A" Well No. 1 in NW NE
Company or Operator Lease
of Sec. 33, T. 23 S, R. 37 E, N. M. P. M., Wildcat Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Present total depth is 6628', plugged back from 9928'. Well is equipped with 13-3/8" csg set at 318' w/300 sacks cement, 9-5/8" csg set at 2950' w/1300 sacks cement, and 7" csg set at 6852' w/700 sacks cement. According to temperature surveys top of cement behind 9-5/8" csg is at 1705' and behind 7" csg at 3715'. Efforts to obtain commercial oil or gas production have been entirely unsuccessful and it is proposed to plug and abandon well in the following manner:

Set retainer at 6400' and squeeze with 50 sacks of cement to close perforations, shoot-off 7" csg at approximately 3650', recover the maximum of 7" csg, shoot-off 9-5/8" csg at approximately 1650', recover the maximum of 9-5/8" casing, build bridge between 1100' and 1050' to plug-off the salt section (top of salt at 1200'), mud to surface with Marco mud, set 4" pipe marker in cement plug on surface with marker to extend 4' above surface.

Work to start on July 10, 1948.

Approved JUL 9 1948, 19____
except as follows:

OIL CONSERVATION COMMISSION.
By Roy Yarbrough
Title Oil & Gas Inspector

Gulf Oil Corporation
Company or Operator
By Chas Taylor
Position Ass't District Sup't.
Send communications regarding well to
Name Chas. Taylor
Address Box 1667, Hobbs, New Mexico

1/25/2020 10:00 AM