




OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plug-back and Casing Perforation	X

July 7, 1948

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation Edith D. Fanning "A" Well No. 1 in the

Company or Operator

Lease

NW NE of Sec. 33, T. 23 S, R. 37 E, N. M. P. M.,

Wildcat Field, Lea County.

The dates of this work were as follows: Started June 22, 1948 and completed June 23, 1948.

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on June 22, 1948

and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

A 7" Lane Wells Type D bridging plug was set at 6650' and 5 sacks of Calseal was dumped on top of plug. Top of Calseal was found at 6628'. After testing plug with 1000# pressure (O.K.), 7" casing was perforated from 6435' to 6490', 6500' to 6515', 6530' to 6560', 6575' to 6595', with six 15/32" holes per foot by Lane Wells. Swabbed load oil and salt water only.

Witnessed by	<u>Frank C. Crawford</u>	<u>Gulf Oil Corporation</u>	<u>Drilling Foreman</u>
	Name	Company	Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

7th day of July 1948

Name Edith D. Fanning

Position Asst District Sup't.

Representing Gulf Oil Corporation
Company or Operator

[Signature]
Notary Public

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks:

APPROVED

Date JUL 9 1948

[Signature]
Title

Handwritten signature: *Handwritten signature*

1000