


## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Resler &amp; Sheldon

Carper Building, Artesia, New Mexico

Company or Operator

Address

Fanning

Well No. 3

in SE NW

of Sec. 33

T. 23S

Lease

R. 37E, N. M. P. M. Mattix Field, Lea County.

Well is 1980 feet south of the North line and 3200 feet west of the East line of the Section

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Edith Fanning Address Eurice, New Mexico

If Government land the permittee is Address

The Lessee is Address

Drilling commenced December 10, 1951 Drilling was completed February 27, 1951

Name of drilling contractor Resler &amp; Sheldon Address

Elevation above sea level at top of casing 3285 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 3516 to 3576 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	OUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
12 1/2				170	R.P.				
8 5/8				1342	R.P.				
7				3440	Float				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15	12 1/2	170	none			
11	8 5/8	1342	25	Halliburton		
8	7	3440	600	Halliburton		

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters — Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
4		SOME #1	150	2-25-51	3516-3576	3576

Results of shooting or chemical treatment Increased production from show to 15 barrels daily

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 210 feet to 1342 feet, and from feet to feet

Cable tools were used from 0 feet to 210 feet, and from 1342 feet to 3576 feet

## PRODUCTION

Put to producing March 2, 1951

The production of the first 24 hours was 15 barrels of fluid of which 100% was oil; % emulsion; % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.

Rock pressure, lbs. per sq. in.

## EMPLOYEES

James Monroe, Driller Carlos Howell, Driller

Glenn Yeater, Driller Harlan Johnson, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rd

day of March, 1951

Notary Public

My Commission expires September 21, 1954

Artesia, New Mexico March 3, 1951

Name Vilas P. Sheldon

Position Partner

Representing Resler &amp; Sheldon Company or Operator

Address Carper Building, Artesia, New Mexico

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
			SECTION 10 1111
-0	35		Sand
35	195		Sand
195	210		Red Rock
210	270		Anhydrite
270	590		No description
590	660		Red Rock Line & Shale
660	700		Red Rock
700	865		Shale & Sand
865	912		Red Sand
912	1055		Red Shale
1055	1095		Red Shale, Anhydrite shells
1095	1160		Red Rock & Anhydrite
1160	1260		Anhydrite
1260	1342		Red Rock & Shells
1342	1365		Salt
1365	1455		Salt & Anhydrite
1455	1970		Salt
1970	2335		Anhydrite & Salt
2335	2400		Salt
2400	2465		Salt & Anhydrite
2465	2650		Anhydrite
2650	2760		Anhydrite & Lime
2760	2965		Anhydrite
2965	3010		Lime & Anhydrite
3010	3378		Lime
3378	3390		Sand
3390	3396		Sand
3396	3410		Lime
3410	3443		Lime
3443	3576		Lime