NUPULAT	NEW MEXICO OIL CONSERVATION Santa Fe, New Mexico	COMMISSION Constant Configuration
	MISCELLANEOUS REPORTS	

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checkin	ag Below
--------------------------------------	----------

REPORT ON BEGINNING DRILLING OPERATIONS		T ON RESULT OF TEST ING SHUT-OFF	x	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT OPERAT	T ON RECOMPLETION		REPORT ON (Other) Completion	x
		December 20, 19	55	Artesia, New	iex100
	÷	(Date)		(Place)	•••••
Following is a report on the				• • •	
ronowing is a report on the	work done and the resu	lts obtained under the hea	aing noted	above at the	
Resler an		its obtained under the hea	aing noted	above at the Fanning	
Resler an		Its obtained under the hea	ading noted		
Company (Company)	d Sheldon			Fanning	33
Company (Company) J. C. Crain Dril (Contribution)	d Sheldon or Operator) Ling Company ractor)	, Well No	4 i	Tenning (Lease) h the	,
Resler an (Company of J. C. Crain Dril (Contr T	d Sheldon or Operator) ling Company ractor) Langlie	, Well No	4 i,	Fanning (Lease)	,
Company (Company) J. C. Crain Dril (Contribution)	d Sheldon or Operator) ling Company ractor) Langlie	, Well No Mattix	4 i,	Tenning (Lease) h the	,

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled to 3670' in 7 7/8" hole. Set 52" @ 3670' and commented w/600 sax comment, the first 400 sax having 45 gel. Let stand 48 hours, then drilled plug to 3670', ran radie active log and perforated from 3557-66', 3591-02', and 3612-26'. Sand oiled w/19,000 gallens Famariss oil and 20,000 lbs. sand. Set bridge plug @ 3546, perforated from 3500-14', 3518-25' and 2527-3%. Sand oiled w/10,000 gallens Famariss oil and 20,000 lbs. sand. Drilled out bridge. Ran tubing as completion.

J. W. Cunni Witnessed by	inghan	J. C. Crai	n Drilling	Company	Tool P	aber
()	Name)	(Company)		(Title)	
Approved: OIL CONSERVAT		N 1	Name	that the inform ny knowledge.	nation given above is tr	ue and complete
	D€C	221955	Representing.	esler and O4 Carper	Sheldon Bldg., Artesia	. Nev Merri
(Title)		(Date)	Address			

i de la compañía de l in the grant of the

 $(1, \frac{2}{2}, \frac{2}{2$

and a state of the state of the