

N.W.O.C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-064118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eva E. Blinebry

9. WELL NO.

18

10. FIELD AND POOL, OR WILDCAT

Teague Blinebry

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

34-23S-37E

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. OIL ☒ WELL GAS ☐ WELL OTHER

2. NAME OF OPERATOR

Carter Foundation Production Company

3. ADDRESS OF OPERATOR

P. O. Box 900, Kermit, Texas 79745

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FNL & 1650' FEL Section 34, T-23-S, R-37-E
Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3276'DF, 3262'GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Plug Back

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4- 1-81: Pulled rods and tubing.

4- 2-81: Set cement retainer @ 3386', cemented with 200 sx Class H cement in two stages. Did not squeeze in two stages. Well squeezed with 188 sx in formation.

4- 3-81: Cemented with 200 sx Neat Class C cement.

4- 6-81: Drilled thru cement retainer to 3580'.

4- 7-81: Drilled thru plug @ 3600'. Drilled to 5446', circulated hole clean.

4- 8-81: Ran Gamma Ray Neutron Log with collar locator from 4300' to 5454'. T.D. @ 5454'. Perforated 2 shots per interval at 4912', 16', 20', 29', 34', 36', 46', 50', 54', 66', 70', 74', 78', 82', 97', 5001', 04', 18', 22', 26', 44', 48', 52', 55', 58'. Acidized with 3500 gals and used 100 ball sealers.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

4-28-81

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 4 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO