

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 064118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

-

7. UNIT AGREEMENT NAME

-

8. FARM OR LEASE NAME

E.C. Hill "M" Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Langlie-Mattix Seven Rivers

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

34-23S-37E

12. COUNTY OR PARISH 13. STATE

Lee

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Carter Foundation Production Company

3. ADDRESS OF OPERATOR

P. O. Box 900, Kermit, Texas 79745

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

990' FNL & 1650' FEL Section 34, T-23-S, R-37-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3276'DF, 3262'GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Plug Back & Recomplete

☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**Completed Operations: Plugged Back and Recompleted in
Langlie-Mattix Seven Rivers Pool.**

- (1) Set cast iron bridge plug @ 7200' w/35' cement on plug.
- (2) Set cast iron bridge plug @ 5500' w/35' cement on plug.
- (3) Perforated 4 squeeze holes @ 3615', pressured to 3000 psi, would not take fluid.
- (4) Set cast iron bridge plug @ 3600' w/35' cement on plug.
- (5) Perforated 2 shots/foot @ 3420', 24', 28', 32', 36', 40', 50', 54', 65', 67', 74', 78', 82', 86', 98', 3502', 07', 12', 22', 26', 30', 41' & 45'.
- (6) Treated through tubing and packer w/4,000 gals. acid, 20,000 gals. gelled water and 40,000# sand w/3400# blocking agent.
- (7) Swabbed load, pulled tubing & removed packer, reran tubing.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert D. Felling

TITLE

Agent

DATE

11-23-76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

NOV 24 1976

**U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO**

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

RECEIVED
OIL & GAS
JAN 2 1976
HONOLULU, H. I.

RECEIVED
OIL & GAS
JAN 2 1976
HONOLULU, H. I.