Form 3160-5 (Novemi er 1983 (Formerly 9-33	DEPARTMEN'	TO STATES JE THE INTERIGENE THE LAND MANAGEMENT	OR (Other instructions verse side)	Budget Bureau No. 1004— Expires August 31, 1985 5. Lease designation and serial LC-064118 6. IF INDIAN, ALLOTTEE OR TRIBE N	XO.
(Do not	SUNDRY NOTICES Use this form for proposals to d Use "APPLICATION F		ack to a different reservoir.		AME
OIL X	GAS WELL OTHER	APR LI)	7. UNIT AGREEMENT NAME	
Plains Petroleum Operating Company				E. C. Hill 'B' Federal	
115 West Wall, Suite 1000, Midland, TX 79701				9. WELL NO.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface				Teaque (Paddock)	
Unit H, 1981' FNL & 810' FEL				Sec 34, T23S, R37E	
14. PERMIT NO.	15. 2	3273' DF	RT, GR, etc.)	12. COUNTY OR PARISH 13. ATATE Lea NM	
16.	Check Appropri	ate Box To Indicate N	ature of Notice, Report, or	r Other Data	
				EQUENT REPORT OF:	
PRACTURE TO SHOOT OR ACTIVE WELL (Other)	REAT MULTIPL TIDIZE ABANDON CHANGE	PLANS	Completion or Reco	ALTERING CARING ABANDONMENT* Etion Altering Caring X Altering Caring Altering Alte	
PAGE 3 OF 4	rork. If well is directionally dr	illed, give subsurface locati	ons and memanred and true ver	tical depths for all markers and zones	perti
<u>10-27-92</u>	Open well, on vacuum.	RIH w/swab. Total bbl	is recovered 237	•	
<u>10-28-92</u>	RIH w/swab. Total bbl	s recovered 200			
10-29-92	OBOP, unset pkr, POOH laying down workstring & pkr. RIH $w/2-3/8$ prod. tbg. ND BOP, set TAC $w/15$ K tension NU WH, PU pump & RIH w/s ame & rods.				
11-10-92	MIRUSU. Unseat pump. POOH w/rods, pump, ND wellhead. Release TAC, POOH w/tbg. LD TAC. RIH w/BPMA, PS, SI 2-3/8" tbg. Tag fill @ 5144' (121'fill). POOH w/tbg, RIH w/2-3/8" notched collar, 1 jt 2-3/8" tbg, 2-3/8" tbg. Close well. Left collar swinging @ 5135'. SDFN. Prep reverse, circulate sand @ RPT time.				
<u>11-11-92</u>	circulation. Clean fi PU & RIH w/2-3/8" BPMA NU wellhead w/Dual Hea	ll to PBTD @ 5265'. Ci , 2-3/8" perf'd tbg SUB d Flange. PU & RIH w/p	rculate hole clean. RD tr. 2-3/8" SN, 156 jts 2-3/8" orimed, repaired pump, 197	Would not load. Establish convent rucks. POOH w/tbg, SN, notched co tbg. EOT @ 5014'. Landed SN @ 4 rods, pony rods, polished rod. S mins. Left pumping to bty.	llar 978′
18. I hereby certify that the foregoing is true and correct Petroleum Engineer				April 19, 1993	
SIGNED				DATE	
(This space f	or Federal or State office use)				
APPROVED CONDITIONS	BY S OF APPROVAL, IF ANY:	TITLE		DATE	