Form 3160-5 (November 1983) (Formerry 9-331) DEPARTMEN. JF THE INTERIOR (Other instructions re-	Form approved. Budget Bureau No. 1004—0: Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL P
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTER OR TRIBE NA
OIL GAS OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Plains Petroleum Operating Company 3. ADDRESS OF OPERATOR	8. FARM OR LEASE NAME E. C. Hill 'B' Federa
415 W. Wall, Suite 1000, Midland, TX 79701	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND FOOL, OR WILDCAT Teague (Blinebry)
1981' FNL & 660'. FEL 810 Unit 14	Sec 34, T23S, R37E
14. FERMIT NO. 15. ELEVATIONS (Show whether DF, ET, GR, etc.) 3273 DF	12. COUNTY OR PARISE 13. STATE Lea NM
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Ot	ther Data
NOTICE OF INTENTION TO:	NT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE REPAIR WELL (Other) TEST WATER SHUT-OFF PRICTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results or Recognished	ALTERING CASING ABANDONMENT* d multiple completion on Well tion Report and Log form.)
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical ***Continuation*** 7. RIH w/ 7" PPI packer w/ SN above top PKR on 2-7/8" WS too. Acidize Paddock perfs w/ PPI PKR w/ 50 gals 15% N Pmp @ 6 BPM. Flush to btm perf. 8. Swab load. Unset PKR, POOH w/tbg, LD PPI PKR, TIH w/ 2-	o 5100'. RU service IEFE HC1 acid/perf.
w/ SN 1 jt f/ btm. 9. RU service co. Frac Paddock w/ 40,000 gals 30# GW + Ottawa at 18 BPM. TOOH w/ 2-7/8" WS.	
10. RU WL. Reperf L. Paddock w/ 2 JSPF, Perf U. Paddock w/	2 JSPF,RD WL.
 RIH w/7" PPI PKR on 2-7/8" WS, Acidize U. Paddock perf gals 15% NEFE HCl acid/perf. Pmp @ 6 BPM. Flush to btm 	s w/ PPI PKR w/ 50 perf.
12. RU swab. Rel. 7" PKR, TOOH w/ 2-7/8" WS, SN, and Pkr.	
13. TIH w/ BPMA, 4' PN, SN on 161 jts 2-3/8" production tb 200 - 3/4" rods.	g. RIH w/ pump and
14. RDWSU. RWTP.	
8. I hereby certify that the foregoing is true and correct SIGNED WILL A WHILE TITLE Petroleum Engineer	DATE 10/16/92
(This space for Federal or State office use) APPROVED BY	DATE