

COPY TO O.C. 2

U. S. LAND OFFICE Las Cruces

U. S. LAND OFFICE
SERIAL NUMBER 064118

LEASE OR PERMIT TO PROSPECT

[illegible]

LOCATE WELL CORRECTLY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company Carter Foundation Production Co. Address P. O. Box 1688, Kermit, Texas

Lessor or Tract Eva E. Blinebry Field Langlie-Mattix State New Mexico

Well No. 10 Sec 35 T. 23-S R. 37-E Meridian NMPM County Lea

Location 330 ft. ^(W) of N Line and 1650 ft. ^(E) of W Line of Section 35 Elevation 3251
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date May 4th, 1955

The summary on this page is for the condition of the well at above date.

Commenced drilling March 12th, 1955 Finished drilling April 30th, 1955

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 3,465 to 3,555 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from 635 to 650 No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
13-3/8	48#	8	Spang	300.18	Tax. Pat.				
10-3/4									
8-1/2				1206.00					
7" CD	20#	8	Spang	344.78	Halliburton				

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
13-3/8	311	200 sacks, neat	Pump & Plug		
7" CD	3448	875 sacks, $\frac{1}{4}$ 3% gel	Pump & Plug		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from Surface feet to 3,555 feet, and from _____ feet to _____ feet.

DATES

May 4th, 1955 Put to producing May 1st, 1955

The production for the first 24 hours was 69 barrels of fluid of which 100 % was oil; No % emulsion; No % water; and No % sediment. Gravity, °Bé. 37.9 @ 60

If gas well, cu. ft. per 24 hours ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in.

EMPLOYEES

L. H. Harner, Driller J. T. Wilcoxson, Driller

J. C. Whaley, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	148	148	Sand and Gravel
148	524	376	Red Beds
524	611	87	Blue & Gray Shale
611	1090	479	Red Beds & Sand
1090	1267	177	Anhydrite and Red Beds
1267	2363	1096	Salt and Anhydrite
2363	2525	162	Anhydrite, Lime, Sand and Red Beds
2525	3288	763	Sand and Limestone
3288	3465	177	Lime, Anhydrite and Sand
3465	3555	90	Sand and some Limestone
			Top Anhydrite 1090 (4 2161)
			Top Salt 1267 (4 1984)
			Base Salt 2363 (4 888)
			Top Yates 2525 (4 726)
			Top Queen 3288 (- 37)
			Top Penrose 3465 (- 214)

