

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-049439 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
GETTY OIL COMPANY

3. ADDRESS OF OPERATOR
P.O. BOX 249, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330°N + W

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
C. D. HIGGS A

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

LANGLIE HATTIX

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SECTION 1, T-26-S, R-37-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3027' DF

12. COUNTY OR PARISH

13. STATE

LEA

NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Layed 30 sack cement plug in and out of 7" casing shoe. W.O.C. tagged cement @ 3079'. Shot 7" casing @ 1496' and pulled; shot 9-5/8" casing @ 412' and pulled; Placed 25 sack cement plug in and out of 7" casing stub. Placed 25 sack cement plug in and out of 9-5/8" casing shoe. Ran 10 sack cement plug in 12-1/2" casing from surface to 22'. Erected surface marker. Hole between plugs filled with mud.

Location cleaned up November 15, 1972, and is ready for inspection.

ILLEGIBLE

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY:

SIGNED C.L. Wade.

C. L. Wade

TITLE AREA SUPERINTENDENT

DATE NOVEMBER 17, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

NOV 29 1972

WLG/lh

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963 - O-685229

847 - 485

RECEIVED

1963 OCT 2

OIL CONSERVATION COM.
HOLDS, N. M.

20185

NOV 1963
U.S. GOVERNMENT PRINTING OFFICE