

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-049439 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

G. D. RIGGS "A"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

LANGLIE MATTIX

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, 26S, 37E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. BOX 249, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

330' FWL & 990' FWL SECTION 1

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3027' D.F.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☒

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pulled rods and pump. Mudded up. Layed 30 sack cement plug in and out of 7" casing shoe @ 3170'. (Open hole interval 3368-3170'.) Ran tubing. Could not find cement. Layed additional 25 sack cement plug. Ran tubing back and tagged top of cement @ 2970'. Shot off 7" casing @ 1296' and pulled. Shot off 8-5/8" @ 775' and pulled. Ran 1330' tubing and layed 25 sack cement plug followed with 4-1/2 bbls. mud. Pulled tubing up to 1115' and layed 25 sack cement plug, followed with 4 bbls. mud. Placed 10 sack cement plug at surface. Erected surface marker.

Location cleaned up November 15, 1972, and is ready for inspection.

18. I hereby certify that the foregoing is true and correct BY:

SIGNED **C.L. Wade:**

C. L. Wade

TITLE

AREA SUPERINTENDENT

DATE **NOV. 17, 1972**

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

NOV 29 1972

J. E. GORDON
AREA DISTRICT ENGINEER

WLG/bh

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983—O-685229

847 - 485

RECEIVED

DEC 10 1983

OIL CONSERVATION COMM.
HOUSTON, TEXAS