

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-049439 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. D. BIGGS "B"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

LANGLIE MATTIX

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SECTION 1, 26S-37E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR
GETTY OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. BOX 249, HOBBS, NEW MEXICO 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FEL, SECTION 1,

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3040 KDS

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Dropped 3 joints 2-1/8" tubing down 5-1/2" casing. Pumped BJ cement plug, followed by 25 sacks cement, followed with 70 bbls. mud. Plug in 5-1/2" casing from 3231' to 2941'. Shot 5-1/2" casing @ 504'. Pulled. Ran tubing down to 527'. Placed 50 sack cement plug from 527' to 297'. (Plug covers 5-1/2" casing stub @ 504' and 8-5/8" casing shoe @ 412'). Ran 10 sack cement plug from surface down to 43'. Erected surface marker.

Location cleaned up November 16, 1972, and is ready for inspection.

18. I hereby certify that the foregoing is true and correct.

ORIGINAL SIGNED BY:

SIGNED **C.L. Wade**

C. L. Wade

TITLE **AREA SUPERINTENDENT**

DATE **NOVEMBER 17, 1972**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

NOV 22 1972

*See Instructions on Reverse Side

WLC/bh

J L GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

947 - 485

RECEIVED

DEC 20 1972

OIL CONSERVATION DIVISION
HOUSTON, TEXAS