

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

030176-B Las Cruces

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C.C. Cagle "C"

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Crosby Devonian

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 3, T-26-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE  
New Mexico

1. OIL ☐ GAS ☐ OTHER ☒ T.A.

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer "D", Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FNL & 660' FWL of Sec. 3

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3004' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-25-73:

Removed well head and master valve. Spotted 10 sack cement plug in top of casing.  
Welded plate on top of casing and installed 4' dry hole marker.  
Well P & A 1-25-73.

January 1965:

Ran casing cutters and cut 5-1/2" casing at 6010'. Spotted 30 sx. cement plug in top of 5-1/2" casing from 5931' to 6057'. Flushed with 23 bbls. salt gel mud. Reset tubing at 3702'. Spotted 30 sx. cement plug in base of 8-5/8" casing from 3600' to 3703'. Filled 8-5/8" casing from surface to 3600' with salt gel mud. Installed well head & T.A.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Supver., Admin. Serv.

DATE 1-26-73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAY 21 1973

\*See Instructions on Reverse Side

J L GORDON  
ACTING DISTRICT ENGINEER