

APPROVED

COPY TO O. C. C. HOBBS

Budget Bureau 42-R358.3.  
Approval expires 12-31-55.

• #3		
Sec. 3		

B-37E

DEC 13 1963

(SUBMIT IN TRIPLICATE)

E. G. HUBBLE  
ACTING DISTRICT ENGINEER  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 030176-BUnit C. C. Cagle "C"

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Remedial work</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 12, 1963

Well No. 3 is located 660 ft. from N line and 660 ft. from W line of sec. 3SW/4 of NW/4 of Sec. 3  
(1/4 Sec. and Sec. No.)26N  
(Twp.)37E  
(Range)NMPM  
(Meridian)Crook County  
(Field)Las  
(County or Subdivision)New Mexico  
(State or Territory)The elevation of the derrick floor above sea level is 3004 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pulled tubing string. Squeezed 5-1/2" cas. perfs. from 8758' to 8811' with 150 sacks cement. Perforated 5-1/2" cas. from 8670' to 8670' with 1 shot per foot. Acidized perfs. with 1500 gals. 15% LSI acid. Tested. Perforated 5-1/2" casing from 8700' to 8720' with 2 shots per foot. Tested. Squeezed perfs. from 8650' to 8720' with 175 sacks cement. Drilled out to 8752'. Perforated 5-1/2" casing from 8740' to 8748' with 2 shots per foot. Acidized perfs. with 500 gals. Spearhead acid. Tested. Squeezed perfs. from 8740' to 8748' with 100 sacks cement. Perforated 5-1/2" casing from 8760' to 8710' with 2 shots per foot. Tested. Well would not flow. Remedial work unsuccessful. Closed well in 11-12-63. Temporarily abandoned effective 12-12-63.

NOTE: Prior to workover, snubbed 12 Hbls. salt water with 3 trips from 3500'.  
No show of gas.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum CorporationAddress P. O. Box 668Hobbs, New MexicoBy R. L. B. P. L. K.Title District Superintendent

1971

1972

1973

1974

1975

1976

1977

1978

1979

1980

1981

1982

1983

1984

1985

1986

1987

1988

1989

1990

1991

1992

1993

1994

1995

1996