


APPROVED

Form 9-331a
(Feb. 1951)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

AUG 18 1961

(SUBMIT IN TRIPLICATE)



J. L. GORDON
ACTING DISTRICT ENGINEER

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Land Office

Lease No.

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. is located 600 ft. from N line and 600 ft. from E line of sec. 3
14 (1/4 Sec. and Sec. No.) 26 (Twp.) 27 (Range) 100 (Meridian)
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run in 17' hole at 1:00 A.M. 8-10-61

As of 8:00, 13-3/4" casing set at 640' and cemented with 400 lbs. of 3-3/4" casing cement. 130 lbs. of 3-3/4" casing cement set at 640' and cemented with 400 lbs. of 3-3/4" casing cement. After 13-3/4" casing set, 130 lbs. of 3-3/4" casing cement set at 640' and cemented with 400 lbs. of 3-3/4" casing cement.

As of 1:00, 17' hole at 1:00 A.M. 8-13-61.

ILLEGIBLE

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Title

03VO-94

00000000

00000000
00000000