

UNITED STATES  
DEPARTMENT OF THE INTERIORSUBMIT IN THE MANNER INDICATED  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to deepen or plug back to a different reservoir.  
See also space 17 below.)

3. LEASE DESIGNATION AND SERIAL NO.

LC 054668

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FARNSWORTH C FEDERAL

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

CROSBY DEVONIAN

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

4-26-37 N M P M

12. COUNTY OR PARISH 13. STATE

LEA

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER DEPLETED

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

Box 68, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

660' FNL x 990' FEL, Sec. 4 (Unit A, NE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3008' R.D.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

On 10/19/66 P+A operations were completed as follows:

Cement Plugs spotted: 25 sq. 8623'-8400' (Pays covered.)  
Shot 5 1/2" casing at 6190', 5970', 5700', and pulled from 5475'.

20 sq plug 5500'-5400'. 25 sq 5200'-5100'. 45 sq 4100'-3850'.  
Shot 8 3/8" casing @ 2025', 1815' and pulled from 1655'.

100 sq plug 1050'-950'. 100 sq 650'-550'. 10 sq at surface and erected P+A marker.

Made final cleanup and restored ground to contour.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt

DATE 11-7-66

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

NOV 14 1966

\*See Instructions on Reverse Side

J L GORDON  
ACTING DISTRICT ENGINEER

044-USGS-16  
1-NSW  
1-SSP  
1-SSP  
1-RRY