

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-054668

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FARNSWORTH "C" Federal

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

CROSBY DEVONIAN GAS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

4-26-37 NMPM

12. COUNTY OR PARISH 13. STATE

LEA

NM

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

San American Petroleum Corp

3. ADDRESS OF OPERATOR

Box 68 Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

660' FNL x 1980' FWL, Sec. 4 (Unit C, NE 1/4 NW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, JR, etc.)

3004' R.D. B

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐  
☐  
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

☒  
☐  
☐  
☐  
☐

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

In accordance w/ Form G-331 submitted 10/20/65, remedial work was performed as follows:

"Set Cast Iron retainers at 8791' and squeezed perforations 8815'-40' w/ 225 sk cement containing 1/2" Inf Plug per sk. Perforated intervals 8754'-58' and 8772'-78' w/ 21SPF. Acidized w/ 500 gallons.

Prior to workover - Well dead

After workover - Flowed 2.8 MMCFPD x 23 BOPD x 337 BWPD.  
TPF 1500, 2964" CH.

OC- 10-13-65  
Comp- 10-25-65

PBD- 8791'  
TD - 8985'

18. I hereby certify that the foregoing is true and correct

SIGNED

Original Signed By

TITLE

Area Foreman

DATE

10-26-65

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

NOV 1 1965

J. L. GORDON  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

014- USGS- Hobbs

1- JWB

1- SUSP

1- RRY