

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
1800 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FNL & FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒



5. LEASE  
Federal LC-030177 (B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
-----

7. UNIT AGREEMENT NAME  
-----

8. FARM OR LEASE NAME  
Sheperd "B"

9. WELL NO.  
3

10. FIELD OR WILDCAT NAME  
Rhodes - Yates

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 5, T-26-S, R-37-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugging and Abandonment Procedure - October 6, 7, 8, 1983. RU PU. NU BOP. Pull 2-3/8" tbg. RIH w/tbg. & 5-1/2" cmt retainer. Set cmt retainer @ 2607'. Pump 25 sx. CL "C" cmt under retainer. Sting out of retainer - Dump 2 sx. CL "C" cmt on top. TOH w/tbg. RU wireline. Perforate w/4 holes @ 1300' w/3-1/8" gun. Pump 75 sx. CL "C" cmt. WOC 4 hrs. TIH w/1260' tbg. no plug found. Pump 150 sx. CL "C" cmt. tagged plug @ approx. 500' LD tbg. Pump 20 sx. Surface plug. RDPU - Dig out cellar. Erect Dry hole marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Arden Walker, Jr. TITLE Prod. Engineer

DATE November 4 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

m

RECEIVED  
AUG 14 1986  
D.C.E.  
HOBBS OFFICE