

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC 030177 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Storage

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

1800 Wilco Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2310 FNL, 330 FEL

7. UNIT AGREEMENT NAME

Rhodes Storage

8. FARM OR LEASE NAME

Shepherd

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Rhodes-Storage-Yates-7 River

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

6-26-37

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2970

12. COUNTY OR PARISH

13. STATE

Lea

New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Rig up pulling unit, load tbg with water, pressure test. Kill well with brine. Displace 50 sx. across perms, pull & stand back 10 stands. Run work string, tag top of cement, displace 36 sx of mud on top of cement. Pull out of hole, shoot off 6 5/8" csg @ 2,000', pull casing. Displace 35 sx cement over stub. Pull 10 jts of 6 5/8" csg and pump 56 bbls mud in well. Pull 6 5/8" casing to 950, displace 35 sx cement in hole (100' plug - 850-950'). Pull 150' of 6 5/8" casing thru well and spot 15 sx top plug of cement to surface. Weld plate on surface casing, set marker & clean up location.

18. I hereby certify that the foregoing is true and correct

SIGNED C. D. Kysar

TITLE Production Clerk

DATE 4-30-75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
APR 30 1975
ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side