

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLI  
(Other instructions  
verse side)Form approved.  
Budget Bureau No. 42-R142  
5. LEASE DESIGNATION AND SERIAL NO.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Storage	7. UNIT AGREEMENT NAME Rhodes Storage
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME Shepherd "B"
3. ADDRESS OF OPERATOR 1800 Wilco Bldg, Midland, Texas 79701	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990 FSL, 330 FEL 2310 990	10. FIELD AND POOL, OR WILDCAT Rhodes-Yates-7 Rivers
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 6, T-26-S, R-37-E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2970	12. COUNTY OR PARISH Lea
	13. STATE NM

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☒CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

RU pulling unit, load tbq w/wtr, pressure test, kill well with brine, displace 50 sx cmt across perfs and 100' above, pull & stand back 10 stds, rn work string, tag top of cmt, displace w/mud on top of cmt, pull out of hole, shoot off 6 5/8" csg @ 2,000', pull csg. Displace 35 sx cmt over stub, pull 10 jts 6 5/8" csg and pmp 50 bbls mud in well, pull 6 5/8" csg to 950', displace 35 sx cmt in hole (100' plug), pull csg up to 50' and spot 15 sx top plug of cmt to surface, weld plate on surface csg, set marker & clean up location.

**AMENDMENT: 1. Cement plugs at stub of 6-5/8" casing and at shoe of 10-3/4" casing should be 50 sacks rather than 35 sacks.**

**2. Changes in the approved plugging program may be necessary to correct well conditions becoming apparent during plugging operations.**

18. I hereby certify that the foregoing is true and correct

SIGNED

*P. O. Kysan*

TITLE

Production Clerk

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED  
AS AMENDED  
MAY 7 1975  
ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side