

Plugged back from 11,895' to 11,500' w/ 50 sx. cement.  
Mud from 11,500' to 11,130'. Cemented from 11,130' to 9930'  
with 25 sx. cement. Perforated 5 $\frac{1}{2}$ " casing 9900' to 9920'.  
Tested perforation under packer. Recovered 2245' slightly  
gas cut mud. No oil.

Plugged hole from 9930' to 9720' w/ 25 sx cement. Set  
Lane-Wells Bridge plug at 9310.  
Perforated 5 $\frac{1}{2}$ " casing from 9225' to 9300' and took Drill  
Stem Test. Recovered show of oil, 395' of gas cut mud,  
665' of gas cut salt water.

Set retainer, squeezed perforation from 9225' to 9300' w/  
200 sx. cement. Drilled out to 9250'. Perforated 5 $\frac{1}{2}$ "  
casing from 9210' to 9240', tested under packer set at  
9145'. No show of oil or gas.

Plugged back 9250' to 9040' w/ 25 sx. of cement. Plugged  
back to 5524' Mud. Plugged back from 5524' to 5314',  
cemented w/ 25 sx.

Perforated 5 $\frac{1}{2}$ " casing from 5190' to 5230'. Test indicates  
no cement around 5 $\frac{1}{2}$ " casing at this point.

Now cementing 5 $\frac{1}{2}$ " casing thru perforation at 5190' to  
5230'. Will re-perforate and test this section.

[illegible]

The above information was obtained from the records of the  
 FBI, New York Office, dated 10/10/68, and is being furnished  
 to you for your information. The above information was obtained  
 from the records of the FBI, New York Office, dated 10/10/68, and  
 is being furnished to you for your information.

1. 在 2000 年 12 月 31 日，公司应计提的坏账准备为 100 万元。

[illegible]