

WELL LOG

Drilled back from 12435' to 12430' with 40 sacks Trinity Inferno Cement.
 Drilled back from 12430' to 12415' with 54 sacks Trinity Inferno Cement.
 Drilled back from 9660' to 9660' with 66 sacks Trinity Inferno Cement.
 Set plug at 7600' with 175 sacks G.F. Cement.
 Rilled up to 7013', reversed circulation and set plug at 7013'. No cement
 pumped out. After cement set at lower located plug at 7906'.
 Drilled back from 7403' to 7013' with 185 sacks #1 Toro Cement. After cement
 set found plug at 7014'. Plug gave way with 6000' pressure. Found hard plug
 at 7016'. Set 15,000' weight on plug with drill pipe. Held OK.
 Perforated formation from 6893' to 7003' with 1 1/2" shot per foot, total
 120 shots. Ran Halliburton Well Stem Test and set packer at 6893'. Tested
 formation from 6893' to 7016'. Tool open one hour. Slight blow air for
 37 minutes. Recovered 30' mud. No flowing pressure.
 Drilled back from 7016' to 6960' with 51 sacks Atlas Regular Cement.
 Drilled back from 6960' to 6960' with 130 sacks Atlas Regular Cement.
 Set plug at 6931'. Found top of plug at 6943'. Perforated from 6135' to
 6940' with 125 sacks shots, 1 shot per foot. Ran Halliburton Well Stem
 Test from 6135' to 6943'. Tool open one hour. Recovered 2100' drilling
 mud and 3041' salty sulphur water. Flowing pressure 1800', and pressure
 1050', formation pressure 0. Cement untreated.
 Drilled back from 6943' to 6943' with 130 sacks Atlas Regular Cement.
 Drilled back from 6905' to 6905' with 130 sacks Atlas Regular Cement.
 Found top of plug at 6940'. Perforated with 217 shots, one shot per foot,
 from 6135' to 6905'. Ran Halliburton Well Stem Test from 6135' to 6940'.
 Tool open one hour. Recovered 1300' drilling mud and 2100' salty sulphur
 water. Flowing pressure 1800', and pressure 2950', no build up pressure.
 Cement untreated.
 Drilled back from 6940' to 6900' with 140 sacks Moor Cement.
 Drilled back from 6925' to 6925' with 130 sacks Moor Cement.
 Set plug from 6900' to surface with 120 sacks Moor Cement.
 Filled up on bar and installed restrooms.
 Well completed July 15, 1946.

NOTE: All depths between plugs filled with mud and water fluid.

ILLEGIBLE