• 001 o	Budget Bureau No. 42-R358. Approval expires 12-31-60.
OFT 9-331 a (Feb. 1951) (SUBMIT IN T	RIPLICATE) Land Office
	HUPBS OFFICENCE C-06.233
PROVED UNITED :	
CTT 1957 GEOLOGICAL	SURVEYOR 11 PH 3 28
QCT 1 1957 GEOLOGICAI	SURVEPO: 21 11 3 240
DUPONT DUPONT ENCLENCINEER	
SUNDRY NOTICES AND	REPORTS ON WELLS
SUNDRI MOTICES AND	
	UBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS SI	UBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WITH OTO TO TEST	UBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DITILE OF DELINE	UBSEQUENT REPORT OF ABANDONMENT
I NOTICE DE INTENTION TO SHOOT ON AGIOTALISTICO	UPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK NATUR	E OF REPORT NOTICE OR OTHER DATA)
(INDICATE ABOVE BY CHECK MARK NATUR	
	October 5 , 195
Well No. 1 is located 1980 ft. from X	line and <b>660</b> ft. from $\left  \begin{matrix} \mathbf{r} \\ \mathbf{W} \end{matrix} \right $ line of sec.
NW/4 Sec. 13 26-5 37-E	
(14 Sec. and Sec. No.)	New Mexico
(Field) (County or Subd	vision) (State or Territory)
eround	
	7967.7.++
The elevation of the <b>distantion</b> above sea level is	
DETAILS (	OF WORK
(State names of and expected depths to objective sands; show sizes, wei	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work)
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300 <sup>6</sup> Elienburger rotary tools and all possible producing in tothing	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with senses will be drillstern tested while
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300 <sup>6</sup> Elienburger rotary tools and all possible producing in tothing	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with senses will be drillstern tested while
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8" Casing at approx. 400 - all	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with seves will be drillstern tested while
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Ellenburger rotary tools and all possible producing in drilling. 13-3/8" Casing at approx. 400" - all 8-5/8" Casing at approx. 3800" for	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' for 5-1/2'' Casing as required	OF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set.
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing is drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' for 5-1/2'' Casing as required	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with somes will be drilletern tested while to be of sufficient weight and grade r depth set.
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Ellenburger rotary tools and all possible producing is drilling. 13-3/8" Casing at approx. 400' - all 8-5/8" Casing at approx. 3800' for 5-1/2" Casing as required Cement to be circulated on 13-3/8" cas cementing 8-5/8" casing to bring top of	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem nportant proposed work) test to be drilled to total depth with somes will be drilletors tosted while to be of sufficient weight and grade r depth set. ing. and sufficient coment used in
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing is drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' for 5-1/2'' Casing as required	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with somes will be drilletern tested while to be of sufficient weight and grade r depth set.
DETAILS ( (State names of and expected depths to objective sands; show sizes, wei ing points, and all other in This operation is a 12, 300' Ellenburger rotary tools and all possible producing is drilling. 13-3/8" Casing at approx. 400' - all 8-5/8" Casing at approx. 3800' for 5-1/2" Casing as required Cement to be circulated on 13-3/8" cas cementing 8-5/8" casing to bring top of	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drilletern tested while i to be of sufficient weight and grade r depth set.
(State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8" Casing at approx. 400° - all 8-5/8' Casing at approx. 3800° - all for 5-1/2" Casing as required for Cement to be circulated on 13-3/8" cas cementing 8-5/8" casing to bring top of Anhydrite.	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler
(State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' - all for 5-1/2' Casing as required for coment to be circulated on 13-3/8'' cas comenting 8-5/8'' casing to bring top of Anbydrite.	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler
(State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8" Casing at approx. 400° - all 8-5/8' Casing at approx. 3800° - all for 5-1/2" Casing as required for Cement to be circulated on 13-3/8" cas cementing 8-5/8" casing to bring top of Anhydrite.	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler
(State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 300' Elienburger rotary tools and all possible producing in drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' - all for 5-1/2' Casing as required for coment to be circulated on 13-3/8'' cas comenting 8-5/8'' casing to bring top of Anbydrite.	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler
DETAILS ( (State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 390' Elienburger rotary tools and all possible producing in drilling. 13-3/8" Casing at approx. 400° - all 8-5/8' Casing at approx. 3800° - all 601 5-1/2" Casing as required for 5-1/2" Casing as required for cement to be circulated on 13-3/8" cas cementing 8-5/8" casing to bring top of Anhydrite.	OF WORK shts, and lengths of proposed casings; indicate mudding jobs, cem- nportant proposed work) test to be drilled to total depth with somes will be drillstorn tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler
(State names of and expected depths to objective sands; show sizes, weiling points, and all other in This operation is a 12, 300' Ellenburger rotary tools and all possible producing in drilling. 13-3/8' Casing at approx. 400' - all 8-5/8' Casing at approx. 3800' - all 601 5-1/2' Casing as required for 5-1/2' Casing as required for cement to be circulated on 13-3/8'' case cementing 8-5/8'' casing to bring top of Anhydrite. I understand that this plan of work must receive approval in writh Company Joe N. Champlin Address Room 4. Exell Building	DF WORK ghts, and lengths of proposed casings; indicate mudding jobs, ceme nportant proposed work) test to be drilled to total depth with somes will be drilletern tested while to be of sufficient weight and grade r depth set. ing, and sufficient cement used in cement to or above top of Rustler ng by the Geological Euryey before operations may be commenced.

The approval granted herein is subject to the following condition:

. --

54 Č.

(1) Before commanding 53" easing, obtain approval of this office as to the amount of commant to be used.