				COPY :	the second second	
Form 9-331 (May 1963) UN ED STATES DEPARTMEIN OF THE INTERIOR (Other Instructions re- DEPARTMEIN OF THE INTERIOR (Other Instructions re- verse side) GEOLOGICAL SURVEY				TE+ For re- 5. LEASE DES	Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND BERIAL NO. LC-030174-B	
SUND	RY NOTICES AND		N WELLS	6. IF INDIAN,	ALLOTTER OR TRIBE NAME	
(Do not use this for	m for proposals to drill or to Jae "APPLICATION FOR PERM	deepen or plug ba-	ck to a different reservoir.	None		
					EMENT NAME	
WELL X WELL OTHER					8. FARM OR LEASE NAME	
TEXACO Inc.					W. H. Rhodes "B" Federal NCT-1	
3. ADDRESS OF OPERATOR					9. WIELL NO.	
P. O. Box 728 Hobbs, New Mexico 88240 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.• See also space 17 below.) At surface					12 10. FIELD AND POOL, OR WILDCAT Rhodas	
Well located 660'	from the South li	ne. and 198	30' from the East	11. SEC., T., SURVE	R., M., OR BLK. AND Y OR AREA	
	26, T-26-S, R-37-E,					
14. PERMIT NO.	15. ELEVATIONS	(Show whether DF,	RT, GR, etc.)	<u>Sec. 26</u> 12. COUNTY	T-26-5 R-37-E OB PARISH 13. STATE	
Regular		06' (DF)		Lea	New Mexico	
16.			Anna of Nation Parast			
	Check Appropriate Box			BSEQUENT REPORT O	.	
NOT	NICE OF INTENTION TO:]	
TEST WATER SHUT-OFF	PULL OR ALTER CA		WATER SHUT-OFF Fracture treatment		EPAIRING WELL	
FRACTURE TREAT Shoot or acidize	ABANDON*		SHOOTING OR ACIDIZING	<u> </u>	BANDONMENT*	
REPAIR WELL	CHANGE PLANS		(Other)			
(Other)			Completion or Rec	sults of multiple co completion Report a	nd Log form.)	
17. DESCRIDE PROPOSED OR CO proposed work. If w nent to this work.)*	OMPLETED OPERATIONS (Clearly rell is directionally drilled, give	state all pertinent subsurface locations	details, and give pertinent d ons and measured and true ve	ates, including esti ertical depths for a	mated date of starting any 11 markers and zones perti-	
The following work has been completed on subject well:					· · · · · · · · · · · · · · · · · · ·	
1. Pulled rods a	nd tubing and clear	n out hole.		· · ·		
2. Set packer at	3043'.					
	hole 3093' to 3272					
brine water f	ollowed by 6000 ga	ls gelled b	rine water with 1	/2// 10-20 s	and/gal followed	
by 6000 gals ; followed with	gelled brine water 1000 gals 15% NEA	W/1 1/2# 1	0-20 sand/gal fol	lowed by 30	O# rock salt plug	
with 6000 gal	s gelled brine wate	er with 1/2	# 10-20 sand/gal	followed w/	ater rollowed 6000 gals gallad	
brine water w	/1 1/2# 10-20 sand,	/gal.	" It is build, but			
4. Run rods and	pump, recover load	and place	well on production	n. Firm		
				n an	· · · · ·	
				1997) 1997 - 1997 1997 - 1997		
				HOLA		
					an Anna	
	115					
18 I handhir anatter that ha	19 foregoing is true and correct	+ .		· · · · · · · · · · · · · · · · · · ·		
18. I hereby certify that the SIGNED	wareging is the and correc		sistant District uperintendent	DATE	April 11, 1968	
(This space for Federal	l or State office use)	<u>ж.с.с.</u>	EPTED FOR RECAR)		
APPROVED BY		AUU. TITLE	1 ILD FUN IL CAL	Lon - DATE	WAR I A RODA	
CONDITIONS OF APP	ROVAL, IF ANY:		District Engineer	aut		
		lei	Con anomalic menter	· .		
			[]	• ·	and the second	

12

.

*See Instructions on Reverse Side