

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <u>Injection well</u>	8. FIRM OR FORMER UNIT
3. ADDRESS OF OPERATOR <u>Leas, Pacific Oil Co., Inc.</u>	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>Leas, Pacific Oil Co., Inc. - Leas, New Mexico 86240</u>	10. FIELD AND POOL, OR WILDCAT
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. Drive in, rig up, pull packer & tubing. Clean out well.
2. Set 5" casing, 10' to 12' rough coated casing.
3. Cement w/200 #. Plug plug w/injection water. 30' to 40'.
4. Set packer, remove out excess cement. Run in 1" tubing.
5. Drill out to 34' to 36' shot 300 # acid.
6. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
7. Set packer, remove out excess cement. Run in 1" tubing.
8. Drill out to 34' to 36' shot 300 # acid.
9. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
10. Set packer, remove out excess cement. Run in 1" tubing.
11. Drill out to 34' to 36' shot 300 # acid.
12. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
13. Set packer, remove out excess cement. Run in 1" tubing.
14. Drill out to 34' to 36' shot 300 # acid.
15. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
16. Set packer, remove out excess cement. Run in 1" tubing.
17. Drill out to 34' to 36' shot 300 # acid.
18. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
19. Set packer, remove out excess cement. Run in 1" tubing.
20. Drill out to 34' to 36' shot 300 # acid.
21. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
22. Set packer, remove out excess cement. Run in 1" tubing.
23. Drill out to 34' to 36' shot 300 # acid.
24. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
25. Set packer, remove out excess cement. Run in 1" tubing.
26. Drill out to 34' to 36' shot 300 # acid.
27. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
28. Set packer, remove out excess cement. Run in 1" tubing.
29. Drill out to 34' to 36' shot 300 # acid.
30. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
31. Set packer, remove out excess cement. Run in 1" tubing.
32. Drill out to 34' to 36' shot 300 # acid.
33. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
34. Set packer, remove out excess cement. Run in 1" tubing.
35. Drill out to 34' to 36' shot 300 # acid.
36. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
37. Set packer, remove out excess cement. Run in 1" tubing.
38. Drill out to 34' to 36' shot 300 # acid.
39. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
40. Set packer, remove out excess cement. Run in 1" tubing.
41. Drill out to 34' to 36' shot 300 # acid.
42. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
43. Set packer, remove out excess cement. Run in 1" tubing.
44. Drill out to 34' to 36' shot 300 # acid.
45. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
46. Set packer, remove out excess cement. Run in 1" tubing.
47. Drill out to 34' to 36' shot 300 # acid.
48. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
49. Set packer, remove out excess cement. Run in 1" tubing.
50. Drill out to 34' to 36' shot 300 # acid.
51. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
52. Set packer, remove out excess cement. Run in 1" tubing.
53. Drill out to 34' to 36' shot 300 # acid.
54. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
55. Set packer, remove out excess cement. Run in 1" tubing.
56. Drill out to 34' to 36' shot 300 # acid.
57. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
58. Set packer, remove out excess cement. Run in 1" tubing.
59. Drill out to 34' to 36' shot 300 # acid.
60. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
61. Set packer, remove out excess cement. Run in 1" tubing.
62. Drill out to 34' to 36' shot 300 # acid.
63. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
64. Set packer, remove out excess cement. Run in 1" tubing.
65. Drill out to 34' to 36' shot 300 # acid.
66. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
67. Set packer, remove out excess cement. Run in 1" tubing.
68. Drill out to 34' to 36' shot 300 # acid.
69. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
70. Set packer, remove out excess cement. Run in 1" tubing.
71. Drill out to 34' to 36' shot 300 # acid.
72. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
73. Set packer, remove out excess cement. Run in 1" tubing.
74. Drill out to 34' to 36' shot 300 # acid.
75. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
76. Set packer, remove out excess cement. Run in 1" tubing.
77. Drill out to 34' to 36' shot 300 # acid.
78. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
79. Set packer, remove out excess cement. Run in 1" tubing.
80. Drill out to 34' to 36' shot 300 # acid.
81. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
82. Set packer, remove out excess cement. Run in 1" tubing.
83. Drill out to 34' to 36' shot 300 # acid.
84. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
85. Set packer, remove out excess cement. Run in 1" tubing.
86. Drill out to 34' to 36' shot 300 # acid.
87. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
88. Set packer, remove out excess cement. Run in 1" tubing.
89. Drill out to 34' to 36' shot 300 # acid.
90. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
91. Set packer, remove out excess cement. Run in 1" tubing.
92. Drill out to 34' to 36' shot 300 # acid.
93. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
94. Set packer, remove out excess cement. Run in 1" tubing.
95. Drill out to 34' to 36' shot 300 # acid.
96. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
97. Set packer, remove out excess cement. Run in 1" tubing.
98. Drill out to 34' to 36' shot 300 # acid.
99. Run in 1" tubing, 10' to 12' rough coated casing, 10' to 12' rough coated casing, 10' to 12' rough coated casing.
100. Set packer, remove out excess cement. Run in 1" tubing.

18. I hereby certify that the foregoing is true and correct

SIGNED C. R. Tilley

TITLE Area Production Manager

DATE 6-16-72

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE C. R. Tilley DATE 6-16-72

APPROVED

*See Instructions on Reverse Side

JUN 19 1972

J. L. GORDON
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485

RECEIVED

OIL & GAS DIVISION
HOOVER, ILL.