	Approval expires 11-30-49.
(orm (2-001 a) (of or ch (042)	Las Cruces
(SUBMIT IN TRIPLICA	<i>Lease</i> No
UNITED STATES	
DEPARTMENT OF THE I	
GEOLOGICAL SURV	E Y I
SUNDRY NOTICES AND REP	ORTS ON WELLS E
-	ORTS ON WELLS
HOHEE OF HELEMENT TO DESCRIPTION	REPORT OF WATER SHUT-OFF
Notice of intention to change faither	REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TECT INTENTION	REPORT OF REDRILLING OR REPAIR
NOTICE OF INTERTION TO THE ETHER	REPORT OF ABANDONMENT
NOTICE OF INTENTION TO ONOOT ON TOTAL	
Notice of intention to read on the	ARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPOR	I. NOTICE. OR OTHER DATA)
(INDICATE ABOVE BY CHECK MARK HATCHE OF HELON	
Auc	ust 8
bi	
Well No is located $660 \text{ ft. from } [S]$ line an SELSUL Soc. 13 $26S = 37E$ (Range)	[W] <u>N.M.P.</u> (Meridian)
	New Mexico
South Leonard (Ext.) Lea (Field) (County or Subdivision)	(State or Territory)
The elevation of the derrick floor above sea level is 3,000	ft.
	ft.
DETAILS OF WOF	
DETAILS OF WOR	acths of proposed casings; indicate mudding jobs, cement-
(State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr	ngths of proposed casings; indicate mudding jobs, cement- oposed work)
DETAILS OF WOF (State names of and expected depthe to objective sends; show sizes, weights, and let ing points, and all other important pr	ngths of proposed casings; indicate mudding jobs, cement- oposed work)
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and ler ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s Mas cemented at a total depth of 1157'. This	ngths of proposed casings; indicate mudding jobs, cement- oposed work) scamless steel casing which leaves 112' of 8-5/8" casing
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and ler ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s Mas cemented at a total depth of 1157'. This	ngths of proposed casings; indicate mudding jobs, cement- oposed work) scamless steel casing which leaves 112' of 8-5/8" casing
DETAILS OF WOF (State names of and expected depthe to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was comented at a total depth of 1157'. This cemented in the hole at the interval from 104;	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'.
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was comented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 1 3250' of 7", 20%. 8 rd. thread seamless steel	ngths of proposed casings; indicate mudding jobs, coment- oposed work) secanless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 250 apples of 8% Jel and 50 sacks of neat cemer	ngths of proposed casings; indicate mudding jobs, coment- oposed work) secanless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was comented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 1 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes ingust 8 a temperature survey of the well was	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of made and the survey indicates
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of made and the survey indicates surface. The coment work
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the and the temperature survey ware performed, by	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of made and the survey indicates surface. The coment work Halliburton. The driller's
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104; On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the and the temperature survey were performed by log indicates tentatively that the T/Salt is	ngths of proposed casings; indicate mudding jobs, coment- opposed work) secanless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and cemented with nt. On the morning of made and the survey indicates surface. The cement work Halliburton. The driller's at 1200'. We will let the
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104; On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the and the temperature survey were performed by log indicates tentatively that the T/Salt is	ngths of proposed casings; indicate mudding jobs, coment- opposed work) secanless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and cemented with nt. On the morning of made and the survey indicates surface. The cement work Halliburton. The driller's at 1200'. We will let the
DETAILS OF WOR (State names of and expected depths to objective sends; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was cemented at a total depth of 1157'. This cemented in the hole at the interval from 104 On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the and the temperature survey were performed by log indicates tentatively that the T/Salt is well stand for 72 hours and will test for a w	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of made and the survey indicates surface. The coment work Halliburton. The driller's at 1200'. We will let the ater shut-off.
DETAILS OF WOF (State names of and expected depthe to objective conds; show sizes, weights, and let ing points, and all other important pr On August 7 we recovered 1045' of the 8-5/8" s was comented at a total depth of 1157'. This cemented in the hole at the interval from 104. On August 7 the well was at a total depth of 3250' of 7", 20%, 8 rd. thread seamless steel 350 sacks of 8% Jel and 50 sacks of neat cemes August 8 a temperature survey of the well was that the top of the cement is 342' below the and the temperature survey were performed by	ngths of proposed casings; indicate mudding jobs, coment- opposed work) scamless steel casing which leaves 112' of 8-5/8" casing 5-1157'. 3250' in hard lime. We ran casing and comented with nt. On the morning of made and the survey indicates surface. The coment work Halliburton. The driller's at 1200'. We will let the ater shut-off. ished as soon as it is available.

Address P. O. Box 872

•

Roswell, New Mexico

	Lav.
By termit	to White.

Title_____Vic~-President _____

ų,

U. S. GOVERNMENT PRINTING OFFICE 16-8437-3

-