

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well    gas ☐ well    other ☐ PxA
2. NAME OF OPERATOR  
Tenneco Oil Company *Midwest Refg. Co.*
3. ADDRESS OF OPERATOR  
San Antonio,  
6800 Park Ten Blvd., Suite 200 N., Texas 78213
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FSL & 330' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) To Replug well

## SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE *NM 100-11*
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Farnsworth
9. WELL NO.  
19
10. FIELD OR WILDCAT NAME  
South Leonard Queen
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sect. 14, T26S, R37E
12. COUNTY OR PARISH  
Lea
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Reenter PxA well and drill out current cement plugs at surface, 1138-1184, 2562-2613' and replug as follows: spot cement plugs 2900-2800', 2075-1975, 1235-1135, 940-840, 605-445, and 20 sx plug at surface. Between each plug 9.5 ppg mud will be spotted. See attached wellbore sketches showing current schematic and proposed schematic after replugging.

**REVISED**

*There will be no new surface disturbance in rework of this well.  
The old existing road and pad will be used.*

*Mark J.*

Subsurface Safety Valve: Make and Type

Set @

11

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Sr. Production Engr

DATE 11-16-79

**APPROVED**

APPROVED BY

JAN 17 1980

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACTING DISTRICT ENGINEER

(This space for Federal or State office use)