

APPROVED
Form 9-3381a
conditions listed on back of this sheet.

OCT 21 1958

T. E. GODFREY
ACTING DISTRICT ENGINEER

Subject to the
(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

30-625-1782
Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office Las Cruces
Lease No. 062384
Unit B

RECEIVED
OCT 27 1958

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Roswell, New Mexico October 23, 1958

Leonard-Federal

Well No. 6 is located 660 ft. from [N] line and 1960 ft. from [E] line of sec. 14

NW 1/4 Sec. 14 26S 37E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Leonard Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

OBJECTIVE: QUEEN SAND

CASING PROGRAM: 275' / Circ. - 8 5/8" - 24# - New
3450' / 150 sx. - 5 1/2" - 15.5# - New

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Leonard Oil Company

Address Box 708 - Roswell, New Mexico

By Timothy T. Leonard

Title Timothy T. Leonard
Sec'y-Treas.

Approved subject of the following condition:

1. The top of the salt formation shall be covered either by using sufficient cement behind the production string or by running a C. V. tool and squeezing at least 100 sacks of cement at the top of the salt formation.