

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MAIN OFFICE OCC

HOBBS OFFICE OCC

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

1957 NOV 20 AM 9:45

1957 DEC 9 AM 10:28

Pool Jalmat Formation Yates County LeaInitial _____ Annual _____ Special X Date of Test 8-17-56Company El Paso Natural Gas Company Lease Elliott Federal Well No. 3Unit N Sec. 17 Twp. 26 S Rge. 37 E Purchaser El Paso Natural Gas Co.Casing 5 1/2 Wt. _____ I.D. _____ Set at 3123 Perf. 2908 To 3002Tubing 2 Wt. _____ I.D. _____ Set at 3063 Perf. _____ To _____Gas Pay: From 2910 To 3002 L _____ xG .655 -GL _____ Bar.Press. 13.2Producing Thru: Casing _____ Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. DualDate of Completion: 5-12-54 Packer None Reservoir Temp. _____

OBSERVED DATA

Tested Through (PROVER) (ORIFICE) (Meter) Type Taps Flange

| Flow Data | | | | | | Tubing Data | | Casing Data | | Duration of Flow Hr. |
|-----------|-------------------------------------|---|----------------|-------------------------|--------------|----------------|--------------|----------------|--------------|----------------------------|
| No. | (<u>PROVER</u>) (Line) Size | (<u>ORIFICE</u>) (Orifice) Size | Press. psig | Diff. h _w | Temp. °F. | Press. psig | Temp. °F. | Press. psig | Temp. °F. | |
| SI | | | | | | <u>757</u> | | <u>818</u> | | <u>24</u> |
| 1. | <u>4</u> | <u>1.500</u> | <u>7.45</u> | <u>4.0</u> | <u>63</u> | <u>730</u> | <u>63</u> | <u>772</u> | | <u>9</u> |
| 2. | <u>4</u> | <u>1.500</u> | <u>7.43</u> | <u>5.0</u> | <u>63</u> | <u>702</u> | <u>63</u> | <u>757</u> | | <u>3 1/2</u> |
| 3. | <u>4</u> | <u>1.500</u> | <u>7.48</u> | <u>6.55</u> | <u>67</u> | <u>629</u> | <u>67</u> | <u>721</u> | | <u>7 1/2</u> |
| 4. | <u>4</u> | <u>1.500</u> | <u>7.43</u> | <u>7.85</u> | <u>71</u> | <u>570</u> | <u>71</u> | <u>693</u> | | <u>6</u> |
| 5. | | | | | | | | | | |

FLOW CALCULATIONS

| No. | Coefficient <u>Flg.</u> (24-Hour) | $\sqrt{h_{wpf}}$ | Pressure psia | Flow Temp. Factor F _t | Gravity Factor F _g | Compress. Factor F _{pv} | Rate of Flow Q-MCFPD @ 15.025 psia |
|-----|---|------------------|------------------|--|-------------------------------------|--|--|
| 1. | <u>13.99</u> | | <u>550.0</u> | <u>.9971</u> | <u>.9571</u> | <u>1.059</u> | <u>1.332</u> |
| 2. | <u>13.99</u> | | <u>552.0</u> | <u>.9971</u> | <u>.9571</u> | <u>1.059</u> | <u>1.661</u> |
| 3. | <u>13.99</u> | | <u>559.5</u> | <u>.9933</u> | <u>.9571</u> | <u>1.055</u> | <u>2.174</u> |
| 4. | <u>13.99</u> | | <u>552.0</u> | <u>.9896</u> | <u>.9571</u> | <u>1.054</u> | <u>2.576</u> |
| 5. | | | | | | | |

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})Specific Gravity Separator Gas Dry Gas
Specific Gravity Flowing Fluid _____
P_c 831.2 P_c 690.9

| No. | <u>PROVER</u> P _t (psia) | P _t ² | F _c Q | (F _c Q) ² | (F _c Q) ² (1-e ^{-s}) | P _w ² | P _c ² -P _w ² | Cal. P _w | P _w P _c |
|-----|--|-----------------------------|------------------|---------------------------------|---|-----------------------------|--|------------------------|----------------------------------|
| 1. | <u>743.2</u> | <u>552.3</u> | | | | <u>616.5</u> | <u>74.4</u> | <u>785.2</u> | <u>.94</u> |
| 2. | <u>714.2</u> | <u>510.1</u> | | | | <u>593.2</u> | <u>97.7</u> | <u>770.2</u> | <u>.93</u> |
| 3. | <u>642.2</u> | <u>412.4</u> | | | | <u>539.0</u> | <u>151.9</u> | <u>734.2</u> | <u>.88</u> |
| 4. | <u>583.2</u> | <u>340.1</u> | | | | <u>498.7</u> | <u>192.2</u> | <u>706.2</u> | <u>.85</u> |
| 5. | | | | | | | | | |

Absolute Potential: 6,200 MCFPD; n .700COMPANY EL PASO NATURAL GAS COMPANYADDRESS Box 1384 - Jal, New Mexico

AGENT and TITLE

R. T. Wright - Petroleum EngineerWITNESSED Conducted by: P. N. RandolphCOMPANY EL PASO NATURAL GAS COMPANY

REMARKS

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressibility factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .