

(SUBMIT IN TRIPLICATE)

U. S. Land Office LOS Cruces Lesse or permit No. 030181-B

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF |
|--|-----|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF REDRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | X., | |
| | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, October 22, 1943

| H. Well | G. No. | Moberly 3 | (b) is loc | ated 660 f | t. from 💦 line | and 1980 ft. | from $\left\{ \begin{array}{c} \mathbf{E} \\ \mathbf{m} \end{array} \right\}$ line of s | ec 17 |
|------------|-----------|--------------|---------------|-------------------|------------------------|---------------------|---|--------------|
| NN 1 | of | NEL Sec. | 17 | 26-8 (Twp.) | 37-8 (Range) | N.M.P.M | | |
| | _ | | | Le | | • | W Maxico | |
| | | (Field) | | () | County or Subdivision) | | (State or Territory) | |

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth 3390', Lime. 8-5/8" casing cemented at 1199' with 200 sacks.

Confirming telephone conversation with your office today, we propose to plug and abandon this well as follows:

Hole will be filled to the surface with good heavy mud, with cement plugs spotted as follows: 15 sacks, 3225' to approximately 3160'; 15 sacks at the base of the salt, from approximately 2810' to 2750'; and 15 sacks in the bottom of the 8-5/8" casing at 1199'. All cement plugs and mud will be pumped in through the drill pipe, and the customary 4" pipe marker cemented in the top of the hole with 10 sacks.

l understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE TEXAS COMPANY

Address Box 1270

Midland, Texas

By

Title District Superintendent

BL CC NMOCC, HODDS, N. M. U. S. GOVERNMENT PRINTING OFFICE 15-8437

с с

the second second second