

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Conoco Inc.
3. ADDRESS OF OPERATOR
P.O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: *1980' FNL & 660' FNL*
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☒
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED
FEB 25 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

5. LEASE
LC-030168 A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
NMFU
8. FARM OR LEASE NAME
Eaves A
9. WELL NO.
9
10. FIELD OR WILDCAT NAME
Scarborough - Yates 7 Rvrs.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 19, T-26S, R-37E
12. COUNTY OR PARISH
Lea
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
2969' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to clean-out, perf., & acidize subject well as follows:

Clean out fill to 3247' if necessary. Spot 126 gal. 15% HCl-NE from 3186' to 3063'. Perf. @ 3120'-25', 3134'-38', 3149'-51', 3155', 3178'-86' w/ 4 JSF. Acidize from 3210' to 3165' w/ 800 gal. 15% HCl-NE. Chemically squeeze w/ 30 bbls. scale inhibitor & flush. Acidize from 3170' to 3090' w/ 800 gal. 15% HCl-NE. Flush well & swab test perfs from 3120' to 3155'. Return well to production

Subsurface Safety Valve: Manu. and type *Verbal approval received 2/22/80 from Jerry Long Set @* Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *W. G. Butler* TITLE *Admin. Supervisor* DATE *2/22/80*

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

MAR 7 1980

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side