

X		

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las Cruces
Lease No. 030168 (b)
Unit C

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		SUBSEQUENT REPORT OF DEEPEN, SET LINER AND RECOMPLETE	XX

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 31, 1962, 19

Eaves B-19
Well No. 2 is located 660 ft. from N line and 1980 ft. from E line of sec. 19.
NW/4 Sec. 19 26S 37E NMPM
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Jalmat Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 2961 ft. KB

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

BEFORE WORKOVER - TD 3040', KB 10', ELEV 2961' KB, CSG PT 7" AT 2740', PAY YATES O.H. 2740-3040', PERF O.H. 2740-3040'. PMP 5 BO, 128 BW, W/5.2 MCFG IN 24 HRS. GOR 1.1, DOR 5 DAILY ALLOW 21 BO. WORK DONE - CLEANED OUT 2780-3040'. DRILLED OUT TO 3222'. RAN G/R SONIC, MICROLATEROLOG, INDUCTION ES LOGS. SET 4 1/2" OD LINER AT 3222' W/125 SX. PERF 7-RIVERS 3150-3162' W/2 JSPP. ACIDIZED PERFS W/3000 GALS 15% LSTNE ACID. 100% WTR OBTAINED. LOG CORRELATION 3150' ON G/R COLLAR IS 3150' ON G/R SONIC AND 3147' ON CORE. RAN CMT RETAINER SET AT 2384'. SQUEEZED PERFS 3150-62', W/200 SX RADIOACTIVE CMT DRILLED OUT RET & CMT 2384-2800'. PERF 7-RIVERS 3172-80' W/4 JSPP. RAN G/R LOG. 3172' ON COLLAR LOG IS 3172' ON SONIC. ACIDIZED PERFS W/2500 GALS 15% LSTNE. AFTER WORKOVER - TD 3222', KB 10', ELEV 2961' KB, CSG PT 4 1/2" OD LINER AT 3222', PAY 7-RIVERS 3172-80', PERF 3172-80'. FL 54 BO, 363 BW, W/72.2 MCFG IN 24 HRS, GOR 1337, DOR 54, CHK 18/64", TP 320 LBS, CP 0 LBS, DAILY ALLOW 36 BO. WORKOVER STARTED 6-26-61, COMP 1-26-62, TSTD 1-28-62.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil CompanyAddress Box 68Eunice, New MexicoBy [Signature]O/2 USGS: NMOC-2; WAM: File
Pan Am-Hbs-2; Atl-Ros-2; STD-Houst, Mid. 1 ea.Title District Superintendent