

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Waterflood Injection
 well well
2. NAME OF OPERATOR
 El Paso Exploration Co.
3. ADDRESS OF OPERATOR
 1800 Wilco Bldg., Midland, Tx 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
 AT SURFACE: 1980' FNL, 660' FWL
 AT TOP PROD. INTERVAL:
 AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Final Recompletion Report

5. LEASE
 LC-030181-C
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
 Moberly "C"
9. WELL NO.
 3
10. FIELD OR WILDCAT NAME
 Rhodes Yates-Seven Rivers
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
 Sec. 21, T26S, R37E
 NMPM
12. COUNTY OR PARISH
 Lea County
13. STATE
 New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
 2976'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Drill to 3363' w/reverse unit.
- Attempted to log open hole, lost tool, fished tool out.
- Run 4" liner (628.04') to 3363', cement w/50 sx. cement.
- Clean out liner
- Perf 3184'-3196' (24 holes), 3202'-3216' (28), 3262'-68' (12), 3278'-82' (8), 3290'-3294' (8), 3308-3316' (15).
- Run 2 3/8" injection string, set Loc-Set pkr @ 2944'.
- Pump 6,500 gal 7 1/2. HCL & 550# salt divertor.
- Swab acid back.
- Manifold for injection.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles L. Alfano TITLE Prod. Engineer DATE January 7, 1985

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
 CONDITIONS OF APPROVAL, IF ANY:

SWR
 JAN 23 1985

Subject to
 Like Approval
 by State

*See Instructions on Reverse Side

Carland

RECEIVED

JAN 24 1985

ROOM
HONORARY OFFICE