

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Texaco Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FEL
AT TOP PROD. INTERVAL: (Unit Letter 'I')
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE

N. M.-25742

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Rhodes Yates Unit

8. PARTIAL OR LEASE NAME

Rhodes Yates Unit

WELL NO.

1

9. SURVEY WILDCAT NAME

Rhodes Yates

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T-26-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

2977' (DF)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up. Pull pump & rods. Install BOP. Pull tubing.
2. Clean out to 3253' (TD).
3. Set Pkr. @ 3017'. Acidize open hole 3093'-3253' w/2500 gals. 20% NEFE Acid in 3-stages using a total of 1300# rock salt between stages.
4. Frac open hole 3090'-3252' w/36,000 gals. 50% Co₂ & 50% gelled 2% KCl acid, 6000# 100 mesh sand, 36,000# 20/40 sand & 24,000# 10/20 sand. Flush w/20 Bbls. Co₂.
5. Install pumping equipment. On 24 Hr. potential test ending 1/26/81, well pumped 5580 & 187BW.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Dist. Supt. DATE 1/26/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JAN 28 1981

U.S. GEOLOGICAL SURVEY
DOSWELL, NEW MEXICO