UNITY STATES SUBMIT IN TRIPLICATION OF THE INTERIOR (Other Instructions of Verse side)

GEOLOGICAL SURVEY

Form approxima.

		Rudget	THE .	. N	0.4	2-R	142
		DESIGN			SER	IAL	80.
ረ	ر م (۲) ـ	0325	10%	.)			

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SHNDRY	NOTICES	AND	REPORTS	ON	WELLS
JULTURI	14011663	-	NEI ONIO	\mathbf{v}_{i}	TILLLI

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

				USE	AFFLICATION FOR FERMIT— for such proposals.)	
1.						7. UNIT AGREEMENT NAME
	WELL	X	GAS WELL		OTHER	
2.	NAME OF	FOPE	RATOR			8. FARM OR LEASE NAME

Texas Pacific Oil Company, Inc. 3. ADDRESS OF OPERATOR

> P. O. Box 4067, 79701 Midland, Texas

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface

Unit M, 990' FSL & 660'

10. FIELD AND POOL, OR WILDOW South Leonard Queen

South Leonard Unit

11. SEC., T., R., M., OR BLE, AND SURVEY OR AREA

9. WELL NO.

15

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2992' DF Lea

≚Sec. 24, 26-S, 37-E 12. COUNTY OR PARISH | 13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS		water shut-off repairing well altering casing shooting or acidizing convert to water injection		
(Other)				(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	[- V]	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of styring any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Work started 3-26-77

- 1. MIRUPU. Pull rods, pump and tubing.
- 2. Run bit, DC and tubing and C.O. to 3500' TD. Drilled new hole to 3540'. POH.
- 3. Ran GR-Caliper log.
- 4. Acidized open hole under packer set at 3298' w/1500 gals Mod 202 acid.
- 5. SI 4-7-77 to 4-20-77.
- 6. 4-20-77 ran plastic coated packer and tubing; packer set at 3303'.
- 7. SI 4-20-77 to 7-1-77.
- 8. 7-1-77 installed surface injection equipment and commenced injection.

18. I hereby certify that the foregoing is true and correct SIGNED III Machine Lack	TITLE Dist.	Operations	Supt.	тъ
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	ACCEPTE	D FOR RECORD	
*Se	e Instructions of	ı Rever leyŞiBe GF HOB	L 13 13. C. T. SURVE EOLOGICAL SURVE BS, NEW MEXICO	