

A 10x10 grid with the number 26 in the center and a dot in the bottom-left corner.

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

Company, The Texas Company Address Box 1720 Fort Worth, Texas

Lessor or Tract W. H. Rhodes (b) Field Rhodes State New Mexico

Well No. 8 Sec. 26 T. 26-S R. 37-E Meridian N.M.P.M. County Lea

Location 660 ft. {N} of S Line and 660 ft. {E} of W Line of Section 26 Elevation 2992' (RF)
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed [Signature] Title Drilg. & Prod. Foreman

Date OCTOBER 18, 1944

The summary on this page is for the condition of the well at above date.

Commenced drilling September 19, 1944 Finished drilling October 10, 1944

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from 3250' to 3310' No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	28#	3rd	Smith	1189'	Halliburton	28# casing	28# casing	28# casing	28# casing
5-1/4"	28#	3rd	Smith	1189'	Halliburton	28# casing	28# casing	28# casing	28# casing
HISTORY OF OFF OF CVS MEET									

MUDDING AND CEMENTING RECORD

	Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
	8-5/8"	1177'	350	Halliburton	--	--
ARK	5-1/2"	3128'	300	Halliburton	--	--

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
4-1/2"	New Mex. Gly. Co.	Liquid Nitro- Glycerine	120	10-13- 1944	3250-3310'	3325'

TOOLS USED

Rotary tools were used from 0 feet to 3325 feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

October 18, 1944, 1944 Put to producing October 16, 1944
The production for the first 16 hours was 224 barrels of fluid of which 100 % was oil; -- %
emulsion; -- % water; and -- % sediment. Gravity, 36.4 A P I
If gas well, cu. ft. per 24 hours -- Gallons gasoline per 1,000 cu. ft. of gas --
Rock pressure, lbs. per sq. in. -- G O R 1318

EMPLOYEES

EMPLOYEES	
Eugene Blount	Driller
A. H. Adam	Driller
P. W. Warrick	Driller
	Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	130	130	Sand, Red Beds & Caliche
130	353	223	Red Beds
353	1088	735	Red Beds & Shells
1088	1132	44	Red Rock
1132	1210	78	Anhydrite
1210	1345	135	Anhydrite & Salt
1345	1549	204	Gyp & Salt
1549	2691	1142	Anhydrite & Salt
2691	2795	104	Salt & Gyp
2795	2840	45	Anhydrite
2840	3250	410	Lime
3250	3310	60	Sandy Lime
3310	3325	15	Lime
		<u>3325</u>	Total Depth

(OVER)
FORMATION RECORD-Continued

