

(SUBMIT IN TRIPLICATE)

Land (Offic	Las	ين	U00	D
Lease	No.	0301	74	(p)	

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Cense	1101 22222	
Unit .		

	DKI NOTIÇES	AND REPORTS ON WELLS	TX
		DEPORT OF WATER SHUT-OFF	
OTICE OF INTENTION TO	DRILL	SUBSTITUTE REPORT OF SHOOTING OR ACIDIZING	·
THE OF INTENTION TO	CHANGE PLANS	DEPORT OF ALTERING CASING	
OF INTENTION TO	TEST WATER SHUT-OFF	DEDPUTING OR REPAIR.	
OF INTENTION TO	RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ABANDONMENT	
TO INTENTION TO	SHOOT OR ACIDIZE	WELL WISTORY	
OTICE OF INTENTION TO	PULL OR ALTER CASING	SUPPLEMENTART WELL THE	
OTICE OF INTENTION TO	O ABANDON WELL		<u> </u>
TOTICE OF INTERIOR		MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
Vell No. 11		t. from S line and 1980ft. from W line of se	
ent cod San.	26 26-S	(Meridian)	
(½ Sec. and Sec. N	(Twp.)	New Mexico	
Rhodes		County or Subdivision) (State or Territory)	
(Field)			
	he derrick floor above s	sea level is 3000 ft.	
The elevation of th	he derrick floor above s	50 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x 5 x	
	D	11	g jobs, cer
	_	t the weights, and lengths of P. F.	
(State names of and expe	ected depths to objective sands; s ing points, s	show sizes, weights, and lengths of proposed work) and all other important proposed work)	
	maan!	Show sizes, weights, and lengths of proposed casings; indicate muddin and all other important proposed work) Depth, 3104 - Line	
Set and ceme Completed at	Total inted 3077° of 5 7:00 P.M. 2-19	Depth, 3104' - Lime 5-1/2" OD casing at 3089' with 30	O sac
Set and ceme Completed at Drilled plus method, usin Tested U.K. Tunderstand that the Company The Address Bo	Total inted 3077° of 5 7:00 P.M. 2-19 at 7:00 P.M. 2 ns 1000# pressur this plan of work must receive a ne Texas Company ox 1270	Depth, 3104 - Line 5-1/2" OD casing at 3089 with 30 5-45. 2-22-45. Tested casing by pressure, before and after drilling plus	O sac ig.
Drilled plus method, using the Company The Address Bo	Total inted 3077* of 5 7:00 P.M. 2-19 at 7:00 P.M. 2 at 7:00 P.M.	Depth, 3104 - Line 5-1/2" OD casing at 3089 with 30 5-45. 2-22-45. Tested casing by pressure, before and after drilling plus	O sac ig.