

NEW MEXICO OIL CONSERVATION COMMISSION

## WELL RECORD

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Drawer "D", Monument, New Mexico.  
Address

R. 37 E, N. M. P. M., Rhodes Field, Lea County

Well is 660 feet south of the North line and 1500 feet west of the East line of Sept. 27

If State land the oil and gas lease is No. B-1451 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_, Address \_\_\_\_\_

If Government land the permittee is\_\_\_\_\_. Address\_\_\_\_\_

The Lessee is \_\_\_\_\_, Address \_\_\_\_\_

Drilling commenced February 15, 1944. Drilling was completed March 10 1944.

Name of drilling contractor. Olson-Blount Drig. Co., Address Oklahoma City, Okla.

Elevation above sea level at top of casing 2996 feet.

The information given is to be kept confidential until \_\_\_\_\_ 19

No. 1, from 3160 to 3245 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

Include data on rate of water inflow and elevation to which water rose in hole

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

[illegible]

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	10 3/4"	701'	175	Halliburton	10.5	7 TONS
8 3/4"	7"	3110'	800	Halliburton	10.4	NONE

Heaving plug—Material\_\_\_\_\_Length\_\_\_\_\_Depth Set\_\_\_\_\_

Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
3 1/2"	10-3 1/2" x 8' 1-3245	Nitroglycerin	170 Qts	3-12-44	3160-3245	3260' TD

Results of shooting or chemical treatment ~~Before shooting made 105.02 Bbls 6 hrs flowing on 1" Choke~~  
~~and after shooting made 305.43 Bbls Oil 10 hrs on 1" Choke~~

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Put to producing March 12, 1944

The production of the first 24 hours was 119.92 barrels of fluid of which 0.00 % was oil: 0.00 %

emulsion; \_\_\_\_\_% water; and \_\_\_\_\_% sediment. Gravity, Be \_\_\_\_\_

If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_ **37.2 Corrected**

Rock pressure, lbs. per sq. in. \_\_\_\_\_

D. Edwards, Driller H. W. Johnson, Driller

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 10

day of April, 1944

*Patricia Mahoney*  
Notary Public

My Commission expires October 24, 1947

~~Monument, New Mexico April 10, 1944~~

Name \_\_\_\_\_

Position Asst. Dist. Supt. *For T. P. P. P.*

Address \_\_\_\_\_

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10	10	Cellar
10	155	145	Sandy Shale
155	255	100	Sand Caliche and Shale
255	375	120	Red Rock
375	617	242	Red Bed and Shale
617	685	68	Red Bed and Shells
685	709	24	Red Bed
709	1090	381	Red Bed
1090	1207	117	Red Bed and Anhydrite
1207	1594	387	Anhydrite and Salt
1594	1745	151	Anhydrite, Salt and Red Rock
1745	2113	368	Anhydrite and Salt
2113	2345	232	Anhydrite, Salt and Potash
2345	2445	100	Anhydrite and Lime
2445	2676	231	Anhydrite, Salt and Gypsum
2676	2800	124	Anhydrite and Gypsum
2800	3110	310	Lime
3110	3164	54	Shale, Shells and Sandy Lime
3164	3180	16	Lime
3180	3246	66	Lime and Sand
3246	3252	6	Lime
3252	3260	8	Hard Lime Total Depth