
Hobbs, N. M.

#### (SUBMIT IN TRIPLICATE)

**GEOLOGICAL SURVEY** 

# UNITED STATES DEPARTMENT OF THE INTERIOR

## Land Office Las Cruces Lease No. 030174 (b)



## SUNDRY NOTICES AND REPORTS ON WELLS BE OFFICE

	DRILL			T REPORT OF WA			, i
NOTICE OF INTENTION TO	CHANGE PLANS		!	T REPORT OF SH			;
•	TEST WATER SHUT-OFF	1 11	1	T REPORT OF AL			1
•	RE-DRILL OR REPAIR WELL	1 11	SUBSEQUEN	T REPORT OF RE	DRILLING	OR REPAIR	
	SHOOT OR ACIDIZE	1 1	SUBSEQUEN	T REPORT OF AE	BANDONM	ENT	
li i	PULL OR ALTER CASING	1 t	SUPPLEMEN	TARY WELL HIST	ORY		
	ABANDON WELL						
HOTICE OF HATELATION TO							
W. H. Rhodes (	b) is located 660 f			Texas			
szł skł sec. 2	7 T-26-S	R-3	7-E	MOM			
(14 Sec. and Sec. No.)		(Ra	ange)	(Merio	•	Mexico	
Rhodes	Lea					State or Territory	
(Field)	(C	county or Su	ipaivision)		(,	state of Territory,	,
	Janeta en abjective sender el		OF WO		ad cauine	o indicate mude	ling jobs, cem
(State names of and expected	ing points at	id all other	important	engins of propos proposed work)	ou casing.	,	ing jobs, com
	ing points, at	id all other	important	,,		APPRO	<u>x.)</u>
FORMATIONS EXT Top of Salt Base of Salt Top of Main Brown Lime	ing points, at	2 <b>9</b> 578" (	D 28#	New 12		(APPRO	X.) Cement d to S
Top of Salt Base of Salt Top of Main Brown Lime	1250° 8- 1250° 5- 2800° 5- 2840° ive oil sand expressions olsen 2811	578" ( L/2" ( xpecto	DD 28# DD 14# ed at a	New 12 New 31	ASING 00' 00'	Cemente 300 Sac	X.) Cement d to S ks
Top of Salt Base of Salt Top of Main Brown Lime First product: Type tools: Drilling Cont	1250° 8- 1250° 5- 2800° 5- 2840° ive oil sand expressions olsen 2811	578 C L/2 C xpacto -Bloud APCO C	od at a pri	New 12 New 31	ASING 80 00' 00' Matel	Camente 300 Sac 3125'.	X.) Cement d to S ks
FORMATIONS EXP Top of Salt Top of Main Brown Lime First product: Type tools: I Drilling Cont:	1250° 8- 2800° 5- 2840° ive oil sand er Rotary ractor: Olsen 2811 Oklah	XPGC CAPCO COMB Combon	oD 28# oD 14# ed at a nt Dri Tower ity, 0	New 12 New 31 Approximating Co	ASING 00' 00' hatel; orpor	Cemente 300 Sac  y 3125*.  ation	Cement d to 5
Top of Salt Base of Salt Top of Main Brown Lime First product: Type tools: Drilling Cont:  Tunderstand that this p	1250° 8- 2840°  ive oil sand exactor: Olsen 2811 Oklah	xpector APCO Soma Coval in wri	oD 28# oD 14# ed at a nt Dri Tower ity, 0	New 12 New 31 Approximating Co	ASING 00' 00' hatel; orpor	Cemente 300 Sac  y 3125*.  ation	Cement d to 5
FORMATIONS EXP Top of Salt Base of Salt Top of Main Brown Lime First product: Type tools: Drilling Cont:  Lunderstand that this pl Company THE Address P.	1250° 8-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250° 5-1250°	xpector Slow APCO Coma Coma Coma Coma Coma Coma Coma Coma	oD 28# oD 14# ed at a nt Dri Tower ity, 0	New 12 New 31 Approximating Co	ASING BE 00' ABTEL: Orpore	Cemente 300 Sac  y 3125*.  ation	Cement d to 5
FORMATIONS EXP Top of Salt Base of Salt Top of Main Brown Lime First product: Type tools: Drilling Cont:  I understand that this pi Company THE Address P.	1250° 8- 2800° 5- 2840°  ive oil sand exactor: Olsen 2811 Oklah lan of work must receive appropriate to the color of the c	xpacto APCO Coma Coval in wri	oD 28# oD 14# ed at a nt Dri Tower ity, 0	New 12 New 31 Approximating Could be klahoma	ASING BE 00' ABTEL: Orpor	Camente 300 Sac 3125*. ation	Cement d to 5 ks

#### NAMES OF THE OWNER OF THE STATE OF THE STATE

#### State of State of Contract Sharps.

### 

ali in a salah di kacamatan di

### TO SERVED STATES

o no matematica de la companio de l La companio de la co

 $(x_1,x_2,\dots,x_n) \in \mathbb{R}^n \times \mathbb$ 

and the second of the second o 

the state of the s