

TOP OF SALT: 1320'

BASE OF SALT: 2750'

ELEV: 2982

660' FNL, 660' FWL

Sec. 30, T-26S, R-37E

125 SX SURFACE PLUG

CIRCLIN PLACE TO 410

7 5/8" 24" @ 361' w/200 SX  
(Circulated)

9.5 ppg  
mud

TOP  
1224'

TOP OF SALT  
1320'

10 SK. CMT PLUG SET  
ACROSS TOP OF SALT  
(1176' - 1465')

BASE OF SALT  
2750'

30 SK. cmt. plug set  
ACROSS TOP OF CIPB + Base of salt  
w/ TOC AT 2656'

CIPB SET  
2656'

Producing in Yates  
3146' - 3202'

Retreivable BP @ 3216

RETAINER  
3260'

3227' - 3306'  
SQUEEZED OFF W/100 SX

4 1/2" 9.5 @ 3312' w/650 SX  
(TOC @ 1224')

TO: 3312'

Completed: 10/1/60

Made By KWT

Checked By

Date 7/24/87

Page of

Conoco Inc.  
Calculation Sheet

Title FAVES A #14  
PROPOSED P+A SKETCH

Job No.

Field

State

RECEIVED

JAN 16 1989

OCD  
HOBBS OFFICE