Form 9-331 Dec. 1973

. Programme of Talanga Series (1944-194) Form Approved. Budget Bureau No. 42-R1424

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	LC-030168 b
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different	N.M.F.U.
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
	Eaves B-1
1. oil gas cother gas other	9. WELL NO.
well Well - other	4
2. NAME OF OPERATOR	5
_ Conoco Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Scarborough · Vates
	11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Box 460, Hobbs, N.M. 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 30, T-265, R-37E
AT SURFACE: 2316' FNL 8990' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 🛩	Len NM
AT TOTAL DEPTH: -	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15 CLEVATIONS (CHOW DE KER AND ME)
KEI OKT, OK OTHER BATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DESCRIPTION APPROVAL TO: CURCEOUENT DEPORT OF	2951'DF
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE	
SHOOT OR ACIDIZE	1 0 G [D]
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	3 1980 change on Form 9-330.)
MULTIPLE COMPLETE	· ·
CHANGE ZONES	OAL CUDVEY
ABANDON* U. S. GEOLOGI	
(other) HOBBS, NEV	V MEXICO
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is d	lirectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertined	
MIRIL 1-7-80 Togged for fill - had 16 fi	Il Cleaned out to 3225.
MIRU 1-7-80. Tagged for fill - had 16' fill. Cleaned out to 3225.	
7 7 7 7 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Perf. 7 Rivers @ 3175-3178', 3181'-3184, 3190'-3193' w/ 2 JSPF (18 holes).	
Set pkr.0 3075'. Pumped in 1500 gal- 13	5% HCI. Flushed WITFW
b swabbed well. Mixed 6 drums TH-814, 1.5	cal TC-122 in Labor TEWA
S SWA ODEA WELL PLIKELI G DYKMS THE OFF, 1-3	720 11 60 203: 11 0-2
pumped into perts. Flushed to perts of 10	5 661.7 FW. WIH W/ MA,
SN, 2 27/8" tbg. Placed well on produ	ction
5/0, 2 2 8 / 20g. / 10 Cen well on pro-	
•	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
Subsurface Safety valve. Marid. and Type	
18. I hereby certify that the foregoing is true and correct	
SIGNED Wee all suffer TITLE Admin. Super	Visor DATE 1/22/80
And the state of t	
(This space for Federal or State of	tice use)
APPROVED BY	DATE
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	
Jan Carl	
	沙拉 美国人名英英
14. G. GEGLOMOLINE AND A STATE OF THE STATE	
HOBBS, NEW MEDICO *See Instructions on Reverse	
*See Instructions on Reverse	Side