

ON COMMISSION
RECEIVED
MAY 28 1951
OIL CONSERVATION COMMISSION
HOODS OFFICE

WELL RECORD OIL CONSERVATION COMMISSION
HOBBS OFFICE

AREA 640 ACRES
LOCATE WELL CORRECTLY

Elevation above sea level at Top of Tubing Head..... **3170'**..... The information given is to be kept confidential until
....., 19.....

No. 3, from.....to..... No. 6, from.....to.....

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10-3/4"	32.75#	New	288'				
7"	23#	New	6241'				

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4"	10-3/4"	301'	150			
8-3/4"	8 7"	6250'	1250			

...Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6890 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing May 26, 1953

OIL WELL: The production during the first 24 hours was 372 barrels of liquid of which 96% was oil; % was emulsion; 4% water; and % was sediment. A.P.I. Gravity 40

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy. 1150'	T. Devonian	T. Ojo Alamo	
T. Salt	T. Silurian	T. Kirtland-Fruitland	
B. Salt	T. Montoya	T. Farmington	
T. Yates 2260'	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres 4090'	T. Granite	T. Dakota	
T. Glorieta 5225'	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs 6150'	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	11.55		Distance from Top Kelly Drive Bushing to Ground				
	40		Caliche & Sand				
	205		Red Shale & Lime				
	540		Red Beds				
	1021		Red Shale				
	1229		Anhydrite, Shale & Lime				
	1309		Salt, Anhydrite & Red Shale				
	1465		Salt & Anhydrite				
	2543		Salt, Shale & Anhydrite				
	2670		Anhydrite				
	2877		Anhydrite & Shale				
	2924		Anhydrite w/Lime Streaks				
	3051		Anhydrite				
	3112		Anhydrite, Lime & Shale				
	3166		Anhydrite				
	3378		Anhydrite & Lime				
	3866		Shale & Lime				
	3889		Lime				
	3918		Cherty Lime				
	3948		Lime				
	3976		Hard Lime				
	4489		Lime				
	4575		Lime & Shale				
	6890		Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 27, 1953

(Date)

Company or Operator Gulf Oil Corporation

Address Box 2167, Hobbs, New Mexico

Name R. G. Emerson

Position or Title Asst. Area Prod. Supt.

DEVIATION - TOTCO SURVEYS

<u>DEPTH</u>	<u>DEG. OFF</u>	<u>DEPTH</u>	<u>DEG. OFF</u>
152'	1/4	4110	0
460'	1/2	4260	1-1/4
675'	3/4	4325	1-1/4
904'	3/4	4670	2
1140'	3/4	4783	1-3/4
1382'	1-1/2	4935	1-1/4
1568	1-1/4	5027	2
1997	3/4	5116	3
2245	2	5209	3
2400	2-1/2	5267	3-1/4
2486	2-3/4	5300	2-1/2
2547	2-1/2	5331	2-1/2
2617	2-1/4	5393	0
2640	2-1/4	5455	3
2740	2-1/8	5515	2-1/2
2824	1-3/4	5593	2-1/2
3076	2-1/2	5668	2-1/4
3140	2-1/2	5852	2
3186	2-1/8	6009	1-1/2
3341	1-1/2	6200	2
3495	1/2	6575	2
3587	0	6650	0
3647	1/8	6731	2
3894	1	6823	2
3955	3/4		