

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

October 6, 1954

Hobbs, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation
(Company or Operator)

Harry Leonard "G**"
(Lease)

McVay and Stafford
(Contractor)

Well No. 42 in the SW 1/4 NW 1/4 of Sec. 4

T. 25-S, R. 38-E, NMPM., Dollarhide-Drinkard Pool, Lea County.

The Dates of this work were as follows: October 3-5, 1954

Notice of intention to do the work (X) (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan (X) (was not) obtained.
(Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 155 Jts (6337') 7" OD 23# Gr N-80 and J-55 SS casing. Set and cemented at 6349' in 2 stages. 1st stage with 1500 sacks 4% Gel and 150 sacks Neat on bottom. Plug at 6249'. Pressure 1200#. 2nd stage thru DV tool at 1171' with 385 sacks 4% Gel. Circulated approximately 20 sacks cement. Job complete by Hovee 2:30PM 10-3-54.

After waiting over 30 hours, tested 7" casing with 1000# for 30 minutes. There was no drop in pressure. Drilled thru DV tool at 1171' and tested DV tool with 1000# for 30 minutes. No drop in pressure. Drilled cement plug from 6249' to 6349' and tested below casing shoe with 800# for 30 minutes. No drop in pressure.

*Formerly designated Harry Leonard "A"

Witnessed by P. K. Parker Gulf Oil Corporation Drilling Foreman
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: E. F. Taylor

Position: Area Supt. of Prod.

Representing: Gulf Oil Corporation

Address: Box 2167, Hobbs, N. M.

(Title)

(Date)