## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

instructions in the Rules and Regulations	of the Commission.	, an agent of the commission, t	zec auditiona
	Indicate Nature of Report by Checking Be	low	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	x
	July 26 1951	Hebba Was Wast	
	(Dato)	Hebbs, New Mexic	e)
Following is a report on the work d	one and the results obtained under the heading r	noted above at the	
Gulf Oil Corporation (Company or Opera	itor)	Harry Leonard "A" (Lease)	
	, Well No39	· · · · · · · · · · · · · · · · · · ·	
	ollarhide-Drinkard Pool,		
	July 21, 1954		
Notice of intention to do the work ( )	(was not) submitted on Form C-102 on	(Cross out incorrect words)	, 19
and approval of the proposed plan (was)			
DETAILI	ED ACCOUNT OF WORK DONE AND RESU	LTS OBTAINED	
lst stage from 6755-6870' w 1050-1000#. Casing pressur 6755-6640' with 2000 gals. Casing pressure 1500# appli Inj rate 168 gpm. Tubing p 4th stage from 6525-6410' w 2100-1600#. Casing pressur Sumbbed 2-1/2 hours and a acid water 2 hours. Gas vo 203 bbls cil, &3 bbls ES an Gas volume 209,800 cu ft.	in 4 stages with total of 8000 grith 2000 gals. Inj rate 126 gpm: 1200# packer pressure applied Inj rate 168 gpm. Tubing pressure 2400-1700#. Casing pressure 2400-1700#. Casing pressure 2400 gals. Inj rate 126 gpm: 1000# applied. Flushed with 2 well kicked off. Flowed 48 bblidume 81,000 cu ft. Tubing pressure 25#. Casing pressure 25#. Casing pressure 25#. Casing pressure 25#. Casing pressure 25#.	a. Tubing pressure 2nd stage from sure 2300-2200#. dith 2000 gals. ssure 1500# applied. a. Tubing pressure 8 bbls oil. slead cil, 59 bbls sure 20#. Flowed 3 3/4" choke 24 hours. ssure packer.	
Witnessed by R. S. Ringon (Name)	Gulf Oil Corporation (Company)	Prilling Foreman	<b>.</b>
Approved: OIL CONSERVATION CO	MMISSION I hereby certify that to the best of my k	t the information given above is true a	and complete
() Jan (	Name	ZJOJEV	
		Area Prod. Supt.	
148.3	Representing	Gulf Gil Gorporation	

(Date)

(Title)

Address Box 21.67, Hobbs, New Mexico