

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 26, 1954  
(Date)Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation  
(Company or Operator)Harry Leonard "A"  
(Lease)D. P. L. Company  
(Contractor)

Well No. 41 in the SE 1/4 NW 1/4 of Sec. 4

T. 25-S, R. 38-E, NMPM, Dollarhide-Queen Pool, Lea County.

The Dates of this work were as follows: July 21-22, 1954

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan ~~(was)~~ (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 116 Jts and piece (3645') 7" OD 20# Gr J-55 SS casing. Set and cemented at 3659' with 795 sacks cement in 2 stages. 1st stage with 211 sacks 4% Gal and 100 sacks Neat on bottom. 2nd stage thru DV tool at 1160' with 384 sacks 4% Gal. Maximum pressure 700#. Circulated approximately 60 sacks cement.

After waiting over 30 hours, tested 7" casing with 1000# for 30 minutes. There was no drop in pressure. Drilled thru DV tool at 1160' and tested DV tool with 1000# for 30 minutes. There was no drop in pressure. Drilled cement plug at 3585' to 3659' and tested cement below shoe with 800# for 30 minutes. There was no drop in pressure.

Witnessed by R. S. Runyon  
(Name)Gulf Oil Corporation  
(Company)Drilling Foreman  
(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: F. Z. Jay

Position: Area Prod. Supt.

Representing: Gulf Oil Corporation

Address: Box 2167, Hobbs, New Mexico

(Title)

(Date)